

## 3-Breaker Parallel Tie Cabinet with Maintenance Bypass Switch (for SU40KX 3-Phase UPS)

MODEL NUMBER: **SUPC2MBP40KX**



### Highlights

- 3 breaker parallel tie cabinet accessory for two Tripp Lite 40kVA 3 phase UPS systems
- Links the output of two UPS systems for 80kVA non-redundant operation
- Integral Maintenance Bypass switch enables UPS maintenance or replacement
- 3 built-in circuit breakers, heavy duty copper buswork
- Compatible Tripp Lite SU40KX 3 phase UPS systems

### Description

Tripp Lite's parallel tie cabinet provides a means for safely paralleling two UPS systems for non-redundant combined mode operation. Non-redundant configuration combines the output of two UPS systems to support twice the output current. Built-in Maintenance Bypass Switch enables UPS maintenance and repair of with no disruption in power to connected equipment. Two input breakers receive incoming power from the UPS and are connected to heavy duty copper buswork and an output breaker rated for the total UPS capacity of the two UPS systems combined. See owners manual and [Tripp Lite Parallel Tie Cabinet with Bypass Panel](#) download for detailed specifications, dimensional drawings, operational flow charts and technical descriptions.

Compatible with two Tripp Lite SU40KX UPS systems.

### Features

- Tripp Lite's parallel tie cabinet provides a means for safely paralleling two UPS systems for non-redundant combined mode operation
- Non-redundant configuration combines the output of two UPS systems to support twice the output current
- Built-in Maintenance Bypass Switch enables UPS maintenance and repair of with no disruption in power to connected equipment
- Two input breakers receive incoming power from the UPS and are connected to heavy duty copper buswork and an output breaker rated for the total UPS capacity of the two UPS systems combined
- Compatible with two Tripp Lite SU40KX UPS systems

## Specifications

| INPUT                              |                           |
|------------------------------------|---------------------------|
| Nominal Input Voltage(s) Supported | 380V AC; 400V AC; 415V AC |
| Voltage Compatibility (VAC)        | 380; 400; 415             |
| PHYSICAL                           |                           |
| Shipping Dimensions (hwd / in.)    | 44 x 31.25 x 13.25        |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|                                     |                         |
|-------------------------------------|-------------------------|
| Shipping Dimensions (hwd / cm)      | 109.5 x 78.4 x 31.75    |
| Shipping Weight (lbs.)              | 225                     |
| Shipping Weight (kg)                | 102                     |
| Unit Dimensions (hwd / in.)         | 42.4 x 30.1 x 11.8      |
| Unit Dimensions (hwd / cm)          | 107.6 x 76.5 x 29.85    |
| Unit Weight (lbs.)                  | 220                     |
| Unit Weight (kg)                    | 99.8                    |
| Form Factors Supported              | Wallmount               |
| <b>WARRANTY</b>                     |                         |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>