


# V23079G1006B301 Product Details



V23079G1006B301



Active

## Communications / Signal PC Board Relays



[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

### Product Highlights:

- V23079 / P2 Relay Series
- DC Actuating System
- Input Voltage = 9 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Current Rating = 2 Amps.

[View all Features](#) | [Find Similar Products](#)

[Previous](#) [1](#) [2](#) [3](#) [4](#) [5](#) ... [20](#) [Next](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

## Documentation & Additional Information

### Product Drawings:

- None Available

### Catalog Pages/Data Sheets:

- [AXICOM Telecom, Signal and RF Relays](#) (PDF, English)
- [TELECOM AND SIGNAL RELAYS](#) (PDF, English)

### Product Specifications:

- None Available

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files:

- None Available

### Additional Information:

- [Product Line Information](#)

### Related Products:

- [Tooling](#)

[List all Documents](#)

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- Termination Type = SMT, J-Legs
- Comment = Delivered in reels

### Electrical Characteristics:

- Actuating System = DC
- Input Voltage (VDC) = 9
- Contact Current Rating (Amps.) = 2
- [Coil Resistance \(?\)](#) = 578
- Coil Power, Nominal (mW) = 140
- Dielectric Between Coil and Contacts (V rms) = 1500

### Body Related Features:

- [Series](#) = V23079 / P2 Relay
- Polarized = Yes

### Contact Related Features:

- Mounting Options = PC Board
- Enclosure = Immersion Cleanable
- [FCC Part 68 Isolation](#) = Yes
- Approved Standards = CSA Certified, UL Recognized
- Contact Material = Silver Nickel, Gold Overlay
- Approx. Dimensions (L x W x H) (mm[in]) = 15.00 x 7.50 x 10.40 [.591 x .296 x .410]
- Option = Bellcore GR1089
- DIP Package Style = Vertical
- Contact Type = Bifurcated
- Pin Configuration = DIP

### Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- [Coil Magnetic System](#) = Polarized, Monostable
- Coil Suppression Diode = Without

### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

### Other:

- Brand = Axicom

