

The T9K7 is an upgraded version of the C702 medium voltage, high current disc pack SCR employing a Bar gate, amplifying gate structure. This amplifying gate design allows the SCR to be reliably operated at high di/dt and high dv/dt conditions in phase control applications.

#### FEATURES:

- Low On-State Voltage
- High di/dt Capability
- High dv/dt Capability
- Hermetic Ceramic Package
- Excellent Surge and I<sup>2</sup>t Ratings

#### APPLICATIONS:

- DC Power Supplies
- Motor Controls
- AC Soft-Starters

#### ORDERING INFORMATION

Select the complete 12 digit Part Number using the table below.  
 EXAMPLE: T9G0161203DH is a 1600V-1200A SCR with 200ma IGT and 12 inch gate and cathode potential leads.

PART	Voltage Rating V <sub>DRM</sub> -V <sub>RSM</sub>	Voltage Code	Current Rating I <sub>tavg</sub>	Current Code	Turn-Off T <sub>q</sub>	Gate I <sub>GT</sub>	Leads
<b>T9G0</b>	1800V*	<b>18</b>	1200A	<b>12</b>	<b>0</b>	<b>3</b>	<b>DH</b>
	1600V	<b>16</b>					
	1400V	<b>14</b>			400us typ.	200ma	12"
	1200V	<b>12</b>					
* limited availability							

**Absolute Maximum Ratings**

Characteristic	Symbol	Rating	Units
Repetitive Peak Voltage	$V_{DRM}-V_{RRM}$	1800	Volts
Average On-State Current, $T_C=70^\circ\text{C}$	$I_{T(Avg.)}$	1750	A
RMS On-State Current, $T_C=70^\circ\text{C}$	$I_{T(RMS)}$	2749	A
Average On-State Current, $T_S=55^\circ\text{C}$	$I_{T(Avg.)}$	1800	A
RMS On-State Current, $T_S=55^\circ\text{C}$	$I_{T(RMS)}$	2827	A
Peak One Cycle Surge Current, 50Hz, $V_R=0V$	$I_{TSM}$	34,000	A
Fuse Cordination $I^2t$ , 50Hz	$I^2t$	5.78E+06	$A^2s$
Critical Rate-of-Rise of On-State Current Repetitive	$di/dt$	150	A/us
Critical Rate-of-Rise of On-State Current Non-Repetitive	$di/dt$	300	A/us
Peak Gate Power, 100us	$P_{GM}$	16	Watts
Average Gate Power	$P_{G(avg)}$	3	Watts
Operating Temperature	$T_j$	-40 to+125	$^\circ\text{C}$
Storage Temperature	$T_{Stg.}$	-50 to+150	$^\circ\text{C}$
Approximate Weight		1	lb
		0.45	Kg
Mounting Force		5000-5500	lbs
		22.7 - 25.0	Knewtons



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (724)925-7272

# T9G0\_\_1203 Select

Phase Control Thyristor

1200 Amperes 1800 Volts


## Electrical Characteristics, Tj=25°C unless otherwise specified

Characteristic	Symbol	Test Conditions	Rating			Units
			min	typ	max	
Repetitive Peak Forward Leakage Current	$I_{DRM}$	Tj=125°C, $V_{DRM}$ =Rated			75	ma
Repetitive Peak Reverse Leakage Current	$I_{RRM}$	Tj=125°C, $V_{RRM}$ =Rated			75	ma
Peak On-State Voltage	$V_{TM}$	Tj=25°C, $I_{TM}$ =1500A			1.20	V
$V_{TM}$ Model, Low Level	$V_0$	Tj=125°C			0.881	V
$V_{TM} = V_0 + r \cdot I_{TM}$	r	15% $I_{TM} - \pi \cdot I_{TM}$			3.74E-04	$\Omega$
$V_{TM}$ Model, 4-Term	A	Tj=125°C			0.437	
$V_{TM} = A + B \cdot \ln(I_{TM}) +$	B	15% $I_{TM} - I_{TSM}$			0.056	
$C \cdot (I_{TM}) + D \cdot (I_{TM})^{1/2}$	C				1.14E-04	
	D				2.18E-03	
Turn-On Delay Time	$t_d$	$V_D = 0.5 \cdot V_{DRM}$ Gate Drive: 40V - 20 $\Omega$		1.5		us
Turn-Off Time	tq	Tj=125°C dv/dt = 20V/us to 80% $V_{DRM}$		400		us
dv/dt <sub>(crit)</sub>	dv/dt	Tj=125°C Exp. Waveform $V_D = 80\%$ Rated	800	1000		V/us
Gate Trigger Current	$I_{GT}$	Tj=25°C $V_D = 12V$	30	100	200	ma
Gate Trigger Voltage	$V_{GT}$		0.8	2.0	4.5	V
Peak Reverse Gate Voltage	$V_{GRM}$				5	V

## Thermal Characteristics

Characteristic	Symbol	Test Conditions	Rating			Units	
			min	typ	max		
Thermal Resistance							
Junction to Case	$R\theta_{jc}$	Double side cooled Centerline Test Method			0.020	°C/Watt	
Case to Sink	$R\theta_{cs}$				0.004	°C/Watt	
Thermal Impedance Model	$Z\theta_{jc}$	Double side cooled					
$Z\theta_{jc}(t) = \Sigma(A(N) \cdot (1 - \exp(-t/\text{Tau}(N))))$		where:	N =	1	2	3	4
			A(N) =	8.83E-04	2.32E-03	4.86E-03	1.20E-02
			Tau(N) =	1.48E-03	1.16E-02	8.12E-02	5.00E-01

### Maximum On-State Voltage Drop



### MAXIMUM TRANSIENT THERMAL IMPEDANCE

