



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. RATING: 50mA @ 12VDC
- ▲ 5. OPERATING FORCE: 160 ± 50 gms
6. TRAVEL: 0.35mm ± 0.1
7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
8. MECHANICAL/ELECTRICAL LIFE 1,000,000 CYCLES MIN.
9. INSULATION RESISTANCE: 100M OHMS MIN @ 500VAC
10. DIELECTRIC STRENGTH: 250VAC FOR 1 MINUTE.
- ▲ 11. CONTACT DOME: STAINLESS STEEL
12. PACKAGING: 500 PCS. PER TAPE & REEL
13. 2002/95/EC (ROHS) COMPLIANT
14. ▲ DENOTES CRITICAL PARAMETER



TITLE TL3300AF160QSSDOME				
SCALE	DATE	DR	DWG	REV
2:1	7/9/2010	BLR	N301100	A

A	19149	Released For Production	7/9/10	BLR
REV	PCR NO	DESCRIPTION	DATE	BY
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED				