

# NCP716

## 80 mA Ultra-Low I<sub>q</sub>, Wide Input Voltage Low Dropout Regulator

The NCP716 is 80 mA LDO Linear Voltage Regulator. It is a very stable and accurate device with ultra-low ground current consumption (4.7  $\mu$ A over the full output load range) and a wide input voltage range (up to 24 V). The regulator incorporates several protection features such as Thermal Shutdown and Current Limiting.

### Features

- Operating Input Voltage Range: 2.5 V to 24 V
- Fixed Voltage Options Available:  
1.2 V to 5.0 V
- Ultra Low Quiescent Current: Max. 4.7  $\mu$ A over Temperature
- $\pm 2\%$  Accuracy over Full Load, Line and Temperature Variations
- PSRR: 60 dB at 100 kHz
- Noise: 200  $\mu$ V<sub>RMS</sub> from 200 Hz to 100 kHz
- Thermal Shutdown and Current Limit Protection
- Available in WDFN6, 2x2x0.8 mm Package
- This is a Pb-Free Device

### Typical Applications

- Portable Equipment
- Communication Systems




Figure 1. Typical Application Schematic



ON Semiconductor®

<http://onsemi.com>

### MARKING DIAGRAMS




WDFN6  
CASE 511BR



XX = Specific Device Code  
M = Date Code

### PIN CONNECTIONS




WDFN6 2x2 mm  
(Top View)

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 16 of this data sheet.

# NCP716



**Figure 2. Simplified Block Diagram**

**Table 1. PIN FUNCTION DESCRIPTION**

Pin No. wDFN6, 2 x 2	Pin Name	Description
6	OUT	Regulated output voltage pin. A small 0.47 $\mu$ F ceramic capacitor is needed from this pin to ground to assure stability.
2	N/C	No connection. This pin can be tied to ground to improve thermal dissipation or left disconnected.
3, EXP	GND	Power supply ground. Exposed pad EXP must be tied with GND pin 3.
4	N/C	No connection. This pin can be tied to ground to improve thermal dissipation or left disconnected.
5	N/C	No connection. This pin can be tied to ground to improve thermal dissipation or left disconnected.
1	IN	Input pin. A small capacitor is needed from this pin to ground to assure stability.

**Table 2. ABSOLUTE MAXIMUM RATINGS**

Rating	Symbol	Value	Unit
Input Voltage (Note 1)	$V_{IN}$	-0.3 to 24	V
Output Voltage	$V_{OUT}$	-0.3 to 5	V
Output Short Circuit Duration	$t_{SC}$	Indefinite	s
Maximum Junction Temperature	$T_J(MAX)$	150	°C
Storage Temperature	$T_{STG}$	-55 to 150	°C
ESD Capability, Human Body Model (Note 2)	$ESD_{HBM}$	2000	V
ESD Capability, Machine Model (Note 2)	$ESD_{MM}$	200	V

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Refer to ELECTRICAL CHARACTERISTICS and APPLICATION INFORMATION for Safe Operating Area.

2. This device series incorporates ESD protection and is tested by the following methods:

ESD Human Body Model tested per AEC-Q100-002 (EIA/JESD22-A114)

ESD Machine Model tested per AEC-Q100-003 (EIA/JESD22-A115)

Latch up Current Maximum Rating tested per JEDEC standard: JESD78

**Table 3. THERMAL CHARACTERISTICS**

Rating	Symbol	Value	Unit
Thermal Characteristics, wDFN6, 2 mm x 2 mm Thermal Resistance, Junction-to-Air	$R_{\theta JA}$	120	°C/W

# NCP716

**Table 4. ELECTRICAL CHARACTERISTICS Voltage version 1.2 V**

$-40^\circ\text{C} \leq T_J \leq 125^\circ\text{C}$ ;  $V_{IN} = 3.0 \text{ V}$ ;  $I_{OUT} = 1 \text{ mA}$ ,  $C_{IN} = C_{OUT} = 1.0 \mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^\circ\text{C}$ . (Note 5)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Operating Input Voltage	$I_{OUT} \leq 10 \text{ mA}$	$V_{IN}$	2.5		24	V
	$10 \text{ mA} < I_{OUT} < 80 \text{ mA}$		3.0		24	
Output Voltage Accuracy	$3.0 \text{ V} < V_{IN} < 24 \text{ V}$ , $0 < I_{OUT} < 80 \text{ mA}$	$V_{OUT}$	1.164	1.2	1.236	V
Line Regulation	$3.0 \text{ V} \leq V_{IN} \leq 24 \text{ V}$ , $I_{OUT} = 1 \text{ mA}$	Reg <sub>LINE</sub>		30		mV
Load Regulation	$I_{OUT} = 0 \text{ mA}$ to $80 \text{ mA}$	Reg <sub>LOAD</sub>		20		mV
Dropout voltage (Note 3)		$V_{DO}$			-	mV
Maximum Output Current	(Note 6)	$I_{OUT}$	110			mA
Ground current	$0 < I_{OUT} < 80 \text{ mA}$ , $-40 < T_A < 85^\circ\text{C}$	$I_{GND}$		3.2	4.2	$\mu\text{A}$
	$0 < I_{OUT} < 80 \text{ mA}$ , $V_{IN} = 24 \text{ V}$				5.8	$\mu\text{A}$
Power Supply Rejection Ratio	$V_{IN} = 3.0 \text{ V}$ , $V_{OUT} = 1.2 \text{ V}$ $V_{PP} = 200 \text{ mV}$ modulation $I_{OUT} = 1 \text{ mA}$ , $C_{OUT} = 10 \mu\text{F}$	PSRR		63		dB
Output Noise Voltage	$V_{OUT} = 1.2 \text{ V}$ , $I_{OUT} = 80 \text{ mA}$ $f = 200 \text{ Hz}$ to $100 \text{ kHz}$	$V_N$		105		$\mu\text{V}_{rms}$
Thermal Shutdown Temperature (Note 4)	Temperature increasing from $T_J = +25^\circ\text{C}$	$T_{SD}$		155		$^\circ\text{C}$
Thermal Shutdown Hysteresis (Note 4)	Temperature falling from $T_{SD}$	$T_{SDH}$	-	25	-	$^\circ\text{C}$

3. Not Characterized at  $V_{IN} = 3.0 \text{ V}$ ,  $V_{OUT} = 1.2 \text{ V}$ ,  $I_{OUT} = 80 \text{ mA}$

4. Guaranteed by design and characterization.

5. Performance guaranteed over the indicated operating temperature range by design and/or characterization production tested at  $T_J = T_A = 25^\circ\text{C}$ . Low duty cycle pulse techniques are used during testing to maintain the junction temperature as close to ambient as possible.

6. Respect SOA

# NCP716

**Table 5. ELECTRICAL CHARACTERISTICS Voltage version 1.5 V**

$-40^\circ\text{C} \leq T_J \leq 125^\circ\text{C}$ ;  $V_{IN} = 3.0 \text{ V}$ ;  $I_{OUT} = 1 \text{ mA}$ ,  $C_{IN} = C_{OUT} = 1.0 \mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^\circ\text{C}$ . (Note 9)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Operating Input Voltage	$I_{OUT} \leq 10 \text{ mA}$	$V_{IN}$	2.5		24	V
	$10 \text{ mA} < I_{OUT} < 80 \text{ mA}$		3.0		24	
Output Voltage Accuracy	$3.0 \text{ V} < V_{IN} < 24 \text{ V}$ , $0 < I_{OUT} < 80 \text{ mA}$	$V_{OUT}$	1.455	1.5	1.545	V
Line Regulation	$3.0 \text{ V} \leq V_{IN} \leq 24 \text{ V}$ , $I_{OUT} = 1 \text{ mA}$	Reg <sub>LINE</sub>		20		mV
Load Regulation	$I_{OUT} = 0 \text{ mA}$ to $80 \text{ mA}$	Reg <sub>LOAD</sub>		20		mV
Dropout voltage (Note 7)						
Maximum Output Current	(Note 10)	$I_{OUT}$	110			mA
Ground current	$0 < I_{OUT} < 80 \text{ mA}$ , $-40 < T_A < 85^\circ\text{C}$	$I_{GND}$		3.2	4.2	$\mu\text{A}$
	$0 < I_{OUT} < 80 \text{ mA}$ , $V_{IN} = 24 \text{ V}$				5.8	$\mu\text{A}$
Power Supply Rejection Ratio	$V_{IN} = 3.0 \text{ V}$ , $V_{OUT} = 1.5 \text{ V}$ $V_{PP} = 200 \text{ mV}$ modulation $I_{OUT} = 1 \text{ mA}$ , $C_{OUT} = 10 \mu\text{F}$	PSRR		60		dB
Output Noise Voltage	$V_{OUT} = 1.5 \text{ V}$ , $I_{OUT} = 80 \text{ mA}$ $f = 200 \text{ Hz}$ to $100 \text{ kHz}$	$V_N$		120		$\mu\text{V}_{rms}$
Thermal Shutdown Temperature (Note 8)	Temperature increasing from $T_J = +25^\circ\text{C}$	$T_{SD}$		155		$^\circ\text{C}$
Thermal Shutdown Hysteresis (Note 8)	Temperature falling from $T_{SD}$	$T_{SDH}$	-	25	-	$^\circ\text{C}$

7. Not Characterized at  $V_{IN} = 3.0 \text{ V}$ ,  $V_{OUT} = 1.5 \text{ V}$ ,  $I_{OUT} = 80 \text{ mA}$

8. Guaranteed by design and characterization.

9. Performance guaranteed over the indicated operating temperature range by design and/or characterization production tested at  $T_J = T_A = 25^\circ\text{C}$ . Low duty cycle pulse techniques are used during testing to maintain the junction temperature as close to ambient as possible.

10. Respect SOA

# NCP716

**Table 6. ELECTRICAL CHARACTERISTICS Voltage version 1.8 V**

$-40^\circ\text{C} \leq T_J \leq 125^\circ\text{C}$ ;  $V_{IN} = 3.0 \text{ V}$ ;  $I_{OUT} = 1 \text{ mA}$ ,  $C_{IN} = C_{OUT} = 1.0 \mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^\circ\text{C}$ . (Note 13)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Operating Input Voltage	$I_{OUT} \leq 10 \text{ mA}$	$V_{IN}$	2.8		24	V
	$10 \text{ mA} < I_{OUT} < 80 \text{ mA}$		3.0		24	
Output Voltage Accuracy	$3.0 \text{ V} < V_{IN} < 24 \text{ V}$ , $0 < I_{OUT} < 80 \text{ mA}$	$V_{OUT}$	1.746	1.8	1.854	V
Line Regulation	$3.0 \text{ V} \leq V_{IN} \leq 24 \text{ V}$ , $I_{OUT} = 1 \text{ mA}$	Reg <sub>LINE</sub>		15		mV
Load Regulation	$I_{OUT} = 0 \text{ mA}$ to $80 \text{ mA}$	Reg <sub>LOAD</sub>		15		mV
Dropout voltage (Note 11)						
Maximum Output Current	(Note 14)	$I_{OUT}$	110			mA
Ground current	$0 < I_{OUT} < 80 \text{ mA}$ , $-40 < T_A < 85^\circ\text{C}$	$I_{GND}$		3.2	4.2	$\mu\text{A}$
	$0 < I_{OUT} < 80 \text{ mA}$ , $V_{IN} = 24 \text{ V}$				5.8	$\mu\text{A}$
Power Supply Rejection Ratio	$V_{IN} = 3.0 \text{ V}$ , $V_{OUT} = 1.8 \text{ V}$ $V_{PP} = 200 \text{ mV}$ modulation $I_{OUT} = 1 \text{ mA}$ , $C_{OUT} = 10 \mu\text{F}$	PSRR		60		dB
Output Noise Voltage	$V_{OUT} = 1.8 \text{ V}$ , $I_{OUT} = 80 \text{ mA}$ $f = 200 \text{ Hz}$ to $100 \text{ kHz}$	$V_N$		140		$\mu\text{V}_{rms}$
Thermal Shutdown Temperature (Note 12)	Temperature increasing from $T_J = +25^\circ\text{C}$	$T_{SD}$		155		$^\circ\text{C}$
Thermal Shutdown Hysteresis (Note 12)	Temperature falling from $T_{SD}$	$T_{SDH}$	-	25	-	$^\circ\text{C}$

11. Not Characterized at  $V_{IN} = 3.0 \text{ V}$ ,  $V_{OUT} = 1.8 \text{ V}$ ,  $I_{OUT} = 80 \text{ mA}$

12. Guaranteed by design and characterization.

13. Performance guaranteed over the indicated operating temperature range by design and/or characterization production tested at  $T_J = T_A = 25^\circ\text{C}$ . Low duty cycle pulse techniques are used during testing to maintain the junction temperature as close to ambient as possible.

14. Respect SOA

## NCP716

**Table 7. ELECTRICAL CHARACTERISTICS Voltage version 2.5 V**

$-40^\circ\text{C} \leq T_J \leq 125^\circ\text{C}$ ;  $V_{IN} = 3.5 \text{ V}$ ;  $I_{OUT} = 1 \text{ mA}$ ,  $C_{IN} = C_{OUT} = 1.0 \mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^\circ\text{C}$ . (Note 17)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Operating Input Voltage	$0 < I_{OUT} < 80 \text{ mA}$	$V_{IN}$	3.5		24	V
Output Voltage Accuracy	$3.5 \text{ V} < V_{IN} < 24 \text{ V}$ , $0 < I_{OUT} < 80 \text{ mA}$	$V_{OUT}$	2.45	2.5	2.55	V
Line Regulation	$V_{OUT} + 1 \text{ V} \leq V_{IN} \leq 24 \text{ V}$ , $I_{OUT} = 1 \text{ mA}$	Reg <sub>LINE</sub>		15		mV
Load Regulation	$I_{OUT} = 0 \text{ mA}$ to $80 \text{ mA}$	Reg <sub>LOAD</sub>		15		mV
Dropout voltage (Note 15)	$V_{DO} = V_{IN} - (V_{OUT(NOM)} - 75 \text{ mV})$ $I_{OUT} = 80 \text{ mA}$	$V_{DO}$		400	640	mV
Maximum Output Current	(Note 18)	$I_{OUT}$	110			mA
Ground current	$0 < I_{OUT} < 80 \text{ mA}$ , $-40 < T_A < 85^\circ\text{C}$	$I_{GND}$		3.2	4.2	$\mu\text{A}$
	$0 < I_{OUT} < 80 \text{ mA}$ , $V_{IN} = 24 \text{ V}$				5.8	$\mu\text{A}$
Power Supply Rejection Ratio	$V_{IN} = 3.5 \text{ V}$ , $V_{OUT} = 2.5 \text{ V}$ $V_{PP} = 200 \text{ mV}$ modulation $I_{OUT} = 1 \text{ mA}$ , $C_{OUT} = 10 \mu\text{F}$	PSRR		60		dB
Output Noise Voltage	$V_{OUT} = 2.5 \text{ V}$ , $I_{OUT} = 80 \text{ mA}$ $f = 200 \text{ Hz}$ to $100 \text{ kHz}$	$V_N$		160		$\mu\text{V}_{rms}$
Thermal Shutdown Temperature (Note 16)	Temperature increasing from $T_J = +25^\circ\text{C}$	$T_{SD}$		155		$^\circ\text{C}$
Thermal Shutdown Hysteresis (Note 16)	Temperature falling from $T_{SD}$	$T_{SDH}$	-	25	-	$^\circ\text{C}$

15. Characterized when  $V_{OUT}$  falls 75 mV below the regulated voltage and only for devices with  $V_{OUT} = 2.5 \text{ V}$

16. Guaranteed by design and characterization.

17. Performance guaranteed over the indicated operating temperature range by design and/or characterization production tested at  $T_J = T_A = 25^\circ\text{C}$ . Low duty cycle pulse techniques are used during testing to maintain the junction temperature as close to ambient as possible.

18. Respect SOA

# NCP716

**Table 8. ELECTRICAL CHARACTERISTICS Voltage version 3.0 V**

$-40^\circ\text{C} \leq T_J \leq 125^\circ\text{C}$ ;  $V_{IN} = 4.0 \text{ V}$ ;  $I_{OUT} = 1 \text{ mA}$ ,  $C_{IN} = C_{OUT} = 1.0 \mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^\circ\text{C}$ . (Note 21)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Operating Input Voltage	$0 < I_{OUT} < 80 \text{ mA}$	$V_{IN}$	4.0		24	V
Output Voltage Accuracy	$4.3 \text{ V} < V_{IN} < 24 \text{ V}$ , $0 < I_{OUT} < 80 \text{ mA}$	$V_{OUT}$	2.94	3.0	3.06	V
Line Regulation	$V_{OUT} + 1 \text{ V} \leq V_{IN} \leq 24 \text{ V}$ , $I_{OUT} = 1 \text{ mA}$	Reg <sub>LINE</sub>		4	10	mV
Load Regulation	$I_{OUT} = 0 \text{ mA}$ to $80 \text{ mA}$	Reg <sub>LOAD</sub>		10	30	mV
Dropout voltage (Note 19)	$V_{DO} = V_{IN} - (V_{OUT(NOM)} - 90 \text{ mV})$ $I_{OUT} = 80 \text{ mA}$	$V_{DO}$		370	580	mV
Maximum Output Current	(Note 22)	$I_{OUT}$	110			mA
Ground current	$0 < I_{OUT} < 80 \text{ mA}$ , $-40 < T_A < 85^\circ\text{C}$	$I_{GND}$		3.2	4.2	$\mu\text{A}$
	$0 < I_{OUT} < 80 \text{ mA}$ , $V_{IN} = 24 \text{ V}$				5.8	$\mu\text{A}$
Power Supply Rejection Ratio	$V_{IN} = 4.3 \text{ V}$ , $V_{OUT} = 3.3 \text{ V}$ $V_{PP} = 200 \text{ mV}$ modulation $I_{OUT} = 1 \text{ mA}$ , $C_{OUT} = 10 \mu\text{F}$	PSRR		58		dB
Output Noise Voltage	$V_{OUT} = 4.3 \text{ V}$ , $I_{OUT} = 80 \text{ mA}$ $f = 200 \text{ Hz}$ to $100 \text{ kHz}$	$V_N$		190		$\mu\text{V}_{rms}$
Thermal Shutdown Temperature (Note 20)	Temperature increasing from $T_J = +25^\circ\text{C}$	$T_{SD}$		155		$^\circ\text{C}$
Thermal Shutdown Hysteresis (Note 20)	Temperature falling from $T_{SD}$	$T_{SDH}$	-	25	-	$^\circ\text{C}$

19. Characterized when  $V_{OUT}$  falls 90 mV below the regulated voltage and only for devices with  $V_{OUT} = 3.0 \text{ V}$

20. Guaranteed by design and characterization.

21. Performance guaranteed over the indicated operating temperature range by design and/or characterization production tested at  $T_J = T_A = 25^\circ\text{C}$ . Low duty cycle pulse techniques are used during testing to maintain the junction temperature as close to ambient as possible.

22. Respect SOA

# NCP716

**Table 9. ELECTRICAL CHARACTERISTICS Voltage version 3.3 V**

$-40^\circ\text{C} \leq T_J \leq 125^\circ\text{C}$ ;  $V_{IN} = 4.3 \text{ V}$ ;  $I_{OUT} = 1 \text{ mA}$ ,  $C_{IN} = C_{OUT} = 1.0 \mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^\circ\text{C}$ . (Note 25)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Operating Input Voltage	$0 < I_{OUT} < 80 \text{ mA}$	$V_{IN}$	4.3		24	V
Output Voltage Accuracy	$4.3 \text{ V} < V_{IN} < 24 \text{ V}$ , $0 < I_{OUT} < 80 \text{ mA}$	$V_{OUT}$	3.234	3.3	3.366	V
Line Regulation	$V_{OUT} + 1 \text{ V} \leq V_{IN} \leq 24 \text{ V}$ , $I_{OUT} = 1 \text{ mA}$	RegLINE		4	10	mV
Load Regulation	$I_{OUT} = 0 \text{ mA}$ to $80 \text{ mA}$	RegLOAD		10	30	mV
Dropout voltage (Note 23)	$V_{DO} = V_{IN} - (V_{OUT(NOM)} - 99 \text{ mV})$ $I_{OUT} = 80 \text{ mA}$	$V_{DO}$		350	560	mV
Maximum Output Current	(Note 26)	$I_{OUT}$	110			mA
Ground current	$0 < I_{OUT} < 80 \text{ mA}$ , $-40 < T_A < 85^\circ\text{C}$	$I_{GND}$		3.2	4.2	$\mu\text{A}$
	$0 < I_{OUT} < 80 \text{ mA}$ , $V_{IN} = 24 \text{ V}$				5.8	$\mu\text{A}$
Power Supply Rejection Ratio	$V_{IN} = 4.3 \text{ V}$ , $V_{OUT} = 3.3 \text{ V}$ $V_{PP} = 200 \text{ mV}$ modulation $I_{OUT} = 1 \text{ mA}$ , $C_{OUT} = 10 \mu\text{F}$	PSRR		60		dB
Output Noise Voltage	$V_{OUT} = 4.3 \text{ V}$ , $I_{OUT} = 80 \text{ mA}$ $f = 200 \text{ Hz}$ to $100 \text{ kHz}$	$V_N$		200		$\mu\text{V}_{rms}$
Thermal Shutdown Temperature (Note 24)	Temperature increasing from $T_J = +25^\circ\text{C}$	$T_{SD}$		155		$^\circ\text{C}$
Thermal Shutdown Hysteresis (Note 24)	Temperature falling from $T_{SD}$	$T_{SDH}$	-	25	-	$^\circ\text{C}$

23. Characterized when  $V_{OUT}$  falls 99 mV below the regulated voltage and only for devices with  $V_{OUT} = 3.3 \text{ V}$

24. Guaranteed by design and characterization.

25. Performance guaranteed over the indicated operating temperature range by design and/or characterization production tested at  $T_J = T_A = 25^\circ\text{C}$ . Low duty cycle pulse techniques are used during testing to maintain the junction temperature as close to ambient as possible.

26. Respect SOA

**Table 10. ELECTRICAL CHARACTERISTICS Voltage version 5.0 V**

$-40^\circ\text{C} \leq T_J \leq 125^\circ\text{C}$ ;  $V_{IN} = 6.0 \text{ V}$ ;  $I_{OUT} = 1 \text{ mA}$ ,  $C_{IN} = C_{OUT} = 1.0 \mu\text{F}$ , unless otherwise noted. Typical values are at  $T_J = +25^\circ\text{C}$ . (Note 29)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Operating Input Voltage	$0 < I_{OUT} < 80 \text{ mA}$	$V_{IN}$	6.0		24	V
Output Voltage Accuracy	$6.0 \text{ V} < V_{IN} < 24 \text{ V}$ , $0 < I_{OUT} < 80 \text{ mA}$	$V_{OUT}$	4.9	5.0	5.1	V
Line Regulation	$V_{OUT} + 1 \text{ V} \leq V_{IN} \leq 24 \text{ V}$ , $I_{OUT} = 1 \text{ mA}$	Reg <sub>LINE</sub>		4	10	mV
Load Regulation	$I_{OUT} = 0 \text{ mA}$ to $80 \text{ mA}$	Reg <sub>LOAD</sub>		10	30	mV
Dropout voltage (Note 27)	$V_{DO} = V_{IN} - (V_{OUT(NOM)} - 150 \text{ mV})$ $I_{OUT} = 80 \text{ mA}$	$V_{DO}$		310	500	mV
Maximum Output Current	(Note 30)	$I_{OUT}$	110			mA
Ground current	$0 < I_{OUT} < 80 \text{ mA}$ , $-40 < T_A < 85^\circ\text{C}$	$I_{GND}$		3.2	4.2	$\mu\text{A}$
	$0 < I_{OUT} < 80 \text{ mA}$ , $V_{IN} = 24 \text{ V}$				5.8	$\mu\text{A}$
Power Supply Rejection Ratio	$V_{IN} = 6.0 \text{ V}$ , $V_{OUT} = 5.0 \text{ V}$ $V_{PP} = 200 \text{ mV}$ modulation $I_{OUT} = 1 \text{ mA}$ , $C_{OUT} = 10 \mu\text{F}$	PSRR		54		dB
Output Noise Voltage	$V_{OUT} = 5.0 \text{ V}$ , $I_{OUT} = 80 \text{ mA}$ $f = 200 \text{ Hz}$ to $100 \text{ kHz}$	$V_N$		220		$\mu\text{V}_{rms}$
Thermal Shutdown Temperature (Note 28)	Temperature increasing from $T_J = +25^\circ\text{C}$	$T_{SD}$		155		$^\circ\text{C}$
Thermal Shutdown Hysteresis (Note 28)	Temperature falling from $T_{SD}$	$T_{SDH}$	-	25	-	$^\circ\text{C}$







27. Characterized when  $V_{OUT}$  falls 150 mV below the regulated voltage and only for devices with  $V_{OUT} = 5.0 \text{ V}$

28. Guaranteed by design and characterization.


29. Performance guaranteed over the indicated operating temperature range by design and/or characterization production tested at  $T_J = T_A = 25^\circ\text{C}$ . Low duty cycle pulse techniques are used during testing to maintain the junction temperature as close to ambient as possible.

30. Respect SOA


## TYPICAL CHARACTERISTICS




## TYPICAL CHARACTERISTICS




**Figure 9.** NCP7163V3 Output Voltage vs.  
Output Current




**Figure 10.** NCP716x50xxx Output Voltage vs.  
Output Current




**Figure 11.** NCP716x25xxx Dropout Voltage vs.  
Output Current



**Figure 12.** NCP716x33xxx Dropout Voltage vs.  
Output Current



**Figure 13.** NCP716x50xxx Dropout Voltage vs.  
Output Current



**Figure 14.** NCP716x12xxx Ground Current vs.  
Input Voltage

## TYPICAL CHARACTERISTICS




Figure 15. NCP716x25xxx Ground Current vs. Input Voltage




Figure 16. NCP716x50xxx Ground Current vs. Input Voltage




Figure 17. NCP716x33xxx Ground Current vs. Input Voltage




Figure 18. NCP716x12xxx Quiescent Current vs. Temperature




Figure 19. NCP716x25xxx Quiescent Current vs. Temperature




Figure 20. NCP716x33xxx Quiescent Current vs. Temperature

## TYPICAL CHARACTERISTICS




Figure 21. NVP716x50xxx Quiescent Current vs. Temperature




Figure 22. NCP716x12xxx PSRR vs. Frequency




Figure 23. NCP716x25xxx PSRR vs. Frequency




Figure 24. NCP716x33xxx PSRR vs. Frequency




Figure 25. NCP716x50xxx PSRR vs. Frequency




Figure 26. NCP716x12xxx Output Spectral Noise Density vs. Frequency

## TYPICAL CHARACTERISTICS




Figure 27. NCP716x25xxx Output Spectral Noise Density vs. Frequency




Figure 28. NCP716x33xxx Output Spectral Noise Density vs. Frequency




Figure 29. NCP716x50xxx Output Spectral Noise Density vs. Frequency




Figure 30. Load Transient Response




Figure 31. Load Transient Response




Figure 32. Load Transient Response

# NCP716

## TYPICAL CHARACTERISTICS




Figure 33. Load Transient Response




Figure 34. Line Transient Response




Figure 35. Line Transient Response




Figure 36. Line Transient Response




Figure 37. Line Transient Response

## APPLICATIONS INFORMATION

The NCP716 is the member of new family of Wide Input Voltage Range Low Dropout Regulators which delivers Ultra Low Ground Current consumption, Good Noise and Power Supply Rejection Ratio Performance.

**Input Decoupling ( $C_{IN}$ )**

It is recommended to connect at least 0.1  $\mu$ F Ceramic X5R or X7R capacitor between IN and GND pin of the device. This capacitor will provide a low impedance path for any unwanted AC signals or Noise superimposed onto constant Input Voltage. The good input capacitor will limit the influence of input trace inductances and source resistance during sudden load current changes.

Higher capacitance and lower ESR Capacitors will improve the overall line transient response.

**Output Decoupling ( $C_{OUT}$ )**

The NCP716 does not require a minimum Equivalent Series Resistance (ESR) for the output capacitor. The device is designed to be stable with standard ceramics capacitors with values of 0.47  $\mu$ F or greater up to 10  $\mu$ F. The X5R and X7R types have the lowest capacitance variations over temperature thus they are recommended.

**Power Dissipation and Heat sinking**

The maximum power dissipation supported by the device is dependent upon board design and layout. Mounting pad configuration on the PCB, the board material, and the ambient temperature affect the rate of junction temperature rise for the part. The maximum power dissipation the NCP716 can handle is given by:

$$P_{D(MAX)} = \frac{[T_{J(MAX)} - T_A]}{R_{\theta JA}} \quad (\text{eq. 1})$$

The power dissipated by the NCP716 for given application conditions can be calculated from the following equations:

$$P_D \approx V_{IN}(I_{GND}(I_{OUT})) + I_{OUT}(V_{IN} - V_{OUT}) \quad (\text{eq. 2})$$

or

$$V_{IN(MAX)} \approx \frac{P_{D(MAX)} + (V_{OUT} \times I_{OUT})}{I_{OUT} + I_{GND}} \quad (\text{eq. 3})$$

**Hints**





$V_{IN}$  and GND printed circuit board traces should be as wide as possible. When the impedance of these traces is high, there is a chance to pick up noise or cause the regulator to malfunction. Place external components, especially the output capacitor, as close as possible to the NCP716, and make traces as short as possible.

## ORDERING INFORMATION

Device	Voltage Option	Marking	Package	Shipping <sup>†</sup>
NCP716MT12TBG	1.2 V	6A	WDFN6 (Pb-Free)	3000 / Tape & Reel
NCP716MT15TG	1.5 V	6C		
NCP716MT18TBG	1.8 V	6D		
NCP716MT25TBG	2.5 V	6E		
NCP716MT30TBG	3.0 V	6F		
NCP716MT33TBG	3.3 V	6G		
NCP716MT50TBG	5.0 V	6H		

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.


## PACKAGE DIMENSIONS

WDFN6 2x2, 0.65P  
CASE 511BR  
ISSUE O

- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
  2. CONTROLLING DIMENSION: MILLIMETERS.
  3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.25 mm FROM THE TERMINAL TIP.
  4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

	MILLIMETERS	
DIM	MIN	MAX
A	0.70	0.80
A1	0.00	0.05
A3	0.20 REF	
b	0.25	0.35
D	2.00 BSC	
D2	1.50	1.70
E	2.00 BSC	
E2	0.90	1.10
e	0.65 BSC	
L	0.20	0.40
L1	---	0.15

## RECOMMENDED MOUNTING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

## LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative