

HF9522

1/2 CUBIC INCH 2 FORM C HERMETICALLY SEALED ELECTRO MAGNETIC RELAY WITH COIL TRANSIENT SUPPRESSION



Features

- Force balanced
- With coil transient suppression
- 10A contacts switching capability
- Failure rate level can be level L
- High ambient applicability
- Hermetically welded and marked by laser

AMBIENT ADAPTABILITY

Ambient grade	I	II	III
Ambient temperature	-55 °C to 85 °C	-55 °C to 85 °C	-65 °C to 125 °C
Humidity			98%, 40 °C
Low air pressure	58.53 kPa	4.39 kPa	4.39 kPa
Sine vibration	Frequency	10 Hz to 1000 Hz	10 Hz to 2000 Hz
	Acceleration	147 m/s ²	196 m/s ²
			294 m/s ²
Shock resistance		490 m/s ²	980 m/s ²
Random vibration		—	20 (m/s ²) ² /Hz
Steady-state acceleration		147 m/s ²	294 m/s ²
			490 m/s ²

CONTACT DATA

Ambient grade	I	II	III
Arrangement			2 C
Contact resistance or voltage drop	Initial max.	0.15Ω	0.01Ω
	After life max.	0.25V	0.125V

Contact and life ratings

Type	Contact load		Electrical life min.
	28Vd.c.	115V a.c. 400Hz Single phase	
Resistive	10A	10A	1 x 10 ⁵ OPS
Inductive	8A	8A	2 x 10 ⁴ OPS
Motor	4A	—	1 x 10 ⁵ OPS
Lamp load	2A	—	1 x 10 ⁵ OPS



HONGFA HERMETICALLY SEALED RELAY

SPECIFICATION

Ambient grade		I	II	III
Insulation resistance min.	Initial	100 MΩ (@ 500 Vd.c.)	100 MΩ (@ 500 Vd.c.)	100 MΩ (@ 500 Vd.c.)
	After life or after testing	50 MΩ (@ 500 Vd.c.)	50 MΩ (@ 500 Vd.c.)	50 MΩ (@ 500 Vd.c.)
Dielectric strength min. (Normal condition)	Between coil & cover	1000 Vr.m.s.	1000 Vr.m.s.	1000 Vr.m.s.
	Between other insulation parts (initial)	1250 Vr.m.s.	1250 Vr.m.s.	1250 Vr.m.s.
	Between other insulation parts (after life testing)	1000 Vr.m.s.	1000 Vr.m.s.	1000 Vr.m.s.
Dielectric strength min. (Low air pressure condition)		350 Vr.m.s.	350 Vr.m.s.	350 Vr.m.s.
Leakage rate max.		1 Pa·cm ³ /s	1 × 10 ⁻¹ Pa·cm ³ /s	1 × 10 ⁻³ Pa·cm ³ /s
Operate time max.				15 ms
Release time max.				15 ms
Mounting style		See the mounting dimension		
Terminals		See the terminal styles		
Work position		Random		
Weight max.		48 g		

COIL DATA

Norminal coil power	Approx.2.8W
---------------------	-------------

Coil Version

Vd.c.

Order Number	Coil voltage		at 25 °C			-65°C to 125°C			Pick-up voltage max.		
	Nominal voltage	Value max.	Coil resistance (Ω) min.	Pick-up voltage max.	Hold voltage max.	Drop-out voltage min.	Pick-up voltage max.	Hold voltage max.	Drop-out voltage min.	High temp. test	Continuous electric test
006	6	7.3	18	3.2	1.6	0.4	4.5	2.3	0.25	5	5.7
012	12	14.5	72	6.5	3.3	0.75	9.0	4.5	0.5	9.9	11.25
028	28	29	280	15.5	5.5	2.3	20.0	7	1.5	21.0	25.0

Notes: We can offer many kinds of coil voltage under the requirement of users.

ORDERING INFORMATION





Type	HF9522	-028	L	-0	2	- II
Order Number	006、012、028					
Failure Rate	L: Failure rate level L (level III products available) ¹⁾ Nil: Without failure rate requirement(level I ,II ,III products available)					
Mounting Style	0, 2, 3 (See the mounting dimension)					
Terminals Style	2, 4 (See " Terminal styles " below)					
Ambient Grade	I : level I II : level II III: level III					

Notes: 1) For the failure rate of L ,the letter "III" of ambient grade level will not appear on relay cover.


OUTLINE DIMENSIONS AND WIRING DIAGRAM

Unit:mm


Outline Dimension




Mounting style 0




Mounting style 2




Mounting style 3



Terminal style 2
(Solder pin)



Terminal style 4
(Solder hook)



Wiring Diagram
(Bottom View)

Disclaimer

This datasheet is for the customers' reference. All the specifications are subject to change without notice.

© Xiamen Hongfa Hermetically Sealed Relays Co., Ltd. All rights of Hongfa are reserved.