

FEATURES

- Excellent h_{FE} linearity:
- Complementary to KTC3876

Maximum Ratings (TA=25 °C unless otherwise noted)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	-35	V
Collector-Emitter Voltage	V_{CEO}	-30	V
Emitter-Base Voltage	V_{EBO}	-5	V
Collector Current -Continuous	I_C	-0.5	A
Collector Power dissipation	P_C	0.15	W
Junction Temperature	T_J	150	°C
Storage Temperature	T_{stg}	-55to +150	°C

KTA1505 (PNP)

ELECTRICAL CHARACTERISTICS (@ Ta=25 °C unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=-100\mu A, I_E=0$	-35			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=-1mA, I_B=0$	-30			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=-100\mu A, I_C=0$	-5			V
Collector cut-off current	I_{CBO}	$V_{CB}=-35V, I_E=0$			-0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=-5V, I_C=0$			-0.1	μA
DC current gain	$h_{FE(1)}$	$V_{CE}=-1V, I_C=-100mA$	70		400	
	$h_{FE(2)}$	$V_{CE}=-6V, I_C=-400mA$	25			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=-100mA, I_B=-10mA$			-0.25	V
Base-emitter voltage	V_{BE}	$V_{CE}=-1V, I_C=-100mA$			-1	V
Transition frequency	f_T	$V_{CE}=-6V, I_C=-20mA$		200		MHz
Collector output capacitance	C_{ob}	$V_{CB}=-6V, I_E=0, f=1MHz$		13		pF

CLASSIFICATION OF h_{FE}

Rank	O	Y	G
Range	70-140	120-240	200-400
Marking	AZO	AZY	AZG

KTA1505 Typical Characteristics

