



NOTE:

1. DISPLAY TYPE: TN
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: TRANSFLECTIVE/POSITIVE
4. DRIVE METHOD: 1/16 DUTY 1/5 BIAS
5. OPERATING VOLTAGE: 4.5V
6. OPERATING TEMP: $-20^{\circ}\text{C} - +70^{\circ}\text{C}$
7. STORAGE TEMP: $-30^{\circ}\text{C} - +80^{\circ}\text{C}$
8. BACKLIGHT TYPE: LED(RED)
9. CONTROLLER: KS0066UP-00
10. UNMARKED TOLERANCE: $\pm 0.3\text{mm}$
11. THE BEZEL IS TO BE PAINTED BLACK

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Vss	Vcc	Vee	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	A	K



TIAN-MA MICROELECTRONICS CO.

6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China

DRAWN BY:	TITLE: TM162GACW7	
CHECKED BY:	DWG NO: G-2	
APPROVED BY:	DWG NAME: TM162GACW7G-2	
CONFIRMED BY:	SHEET NO: 01	