



60×40×22

NE720

CQC 03001003498

Features
<ul style="list-style-type: none"> ▪ Magnet latching relay. ▪ High sensitivity & reliability. ▪ Well anti-shock and anti-vibration. ▪ Heavy contact load.

Ordering Information	
NE720 <u>A</u> <u>Z</u> <u>DC12V</u> <u>D</u> 1 2 3 4 5	
1 Part number: NE720	3 Enclosure: Z: Dust cover
2 Contact arrangement: A:1A; B:1B	4 Coil rated voltage(V): DC:6,12, 24
	5 Coil:NIL:singal coil ;D:double coils

Contact Data	
Contact Arrangement	1A (SPSTNO) , 1B (SPSTNC)
Contact Material	AgSnO ₂
Contact Rating(resistive)	100Amax/240VAC
Max. Switching Power	23000VA(COSΦ=1) 2300VA(COSΦ=0.4)
Max. Switching Voltage	400VAC Max. Switching Current:100A
Contact Resistance or Voltage drop	<1mΩ Item 4.12 of IEC 61810-7
Operation life	Electrical (Rated load) 10 ⁴ Item 4.30 of IEC 61810-7
	Mechanical (No load) 10 ⁶ Item 4.31 of IEC 61810-7

Coil Parameter								
Dash numbers	Coil rated voltage VDC	Coil resistance Ω ±10%	Switching voltage VDC (<80% of rated voltage)	Operating voltage range VDC	Pulse magnitude ms	Coil power consumption W	Operate Time ms	Reset Time ms
2 COIL								
006-4500	6	2×8	<4.8	4.9~10	>36	4.5	<12	<6
012-4500	12	2×32	<9.6	9.8~20				
024-4500	24	2×130	<19.2	19.7~40				
1 COIL								
006-2250	6	16	<4.8	4.9~10	>36	2.25	<12	<6
012-2250	12	64	<9.6	9.8~20				
024-2250	24	260	<19.2	19.7~40				

CAUTION: 1.When latching relays are installed in equipment, the latch and reset coil should not be pulsed simultaneously. Coil should not be pulsed with less than the nominal coil voltage and pulse width should be a minimum of three times the specified operate time of the relay. If these conditions are not followed, it is possible for the relay to in be the magnetically neutral position .
 2.Switching voltage is for test purpose only and are no to be used as design criteria.

Operation condition		
Insulation Resistance	1000MΩ min (at 500VDC)	Item 7 of IEC 61810-5
Dielectric Strength	50Hz 2000V surge Voltage4kV	Item 6 and 8 of IEC 61810-5
Between contact and coil	50Hz 4000V surge Voltage 12kV	Item 6 and 8 of IEC 61810-5
Creepage distance	8.4mm	Addenda B of IEC61810-5
Shock resistance	Functional 100m/s ² ;Survival:1000 m/s ² 11ms	IEC68-2-27 Test Ea
Vibration resistance	10~55Hz Double amplitude 1.5mm	IEC68-2-6 Test Fc
Terminals strength	5N; 2.5N • m	IEC68-2-21 Test Ua1and Ud
Solderability	235℃ ±2℃ 3±0.5s	IEC68-2-20 Test Ta method 1
Ambient Temperature	-40~85℃	
Relative Humidity	85% (at 40℃)	IEC68-2-3Test Ca
Mass	82g	

Safety approvals	
Safety approval	CQC
Load	100A/220VAC

Dimensions mm /inch

Dimensions

Mounting (Bottom view)

Wiring diagram

Notes: A:NC side B:NO side

NOTES 1).Dimensions are in millimeters.
 2).Inch equivalents are given for general information only.
 3).Relays shall have plus(+) or plus(+) and minus(-) signs placed on the circuit diagram as shown.