



CHENMKO ENTERPRISE CO.,LTD

SURFACE MOUNT

N-Channel Enhancement Mode Field Effect Transistor

VOLTAGE 120 Volts CURRENT 10 Ampere

CHM1012PAPT

Lead free devices

APPLICATION

- * Servo motor control.
- * Power MOSFET gate drivers.
- * Other switching applications.


FEATURE

- * Small package. (TO-252A)
- * Super high dense cell design for extremely low R_{DSON}.
- * High power and current handing capability.


CONSTRUCTION

- * N-Channel Enhancement

CIRCUIT



TO-252A



1 Gate
2 Source
3 Drain (Heat Sink)

Dimensions in inches and (millimeters)

TO-252A

Absolute Maximum Ratings

T_A = 25°C unless otherwise noted

Symbol	Parameter	CHM1012PAPT	Units
V _{DSS}	Drain-Source Voltage	120	V
V _{GSS}	Gate-Source Voltage	±20	V
I _D	Maximum Drain Current - Continuous	10	A
	- Pulsed (Note 3)	40	
P _D	Maximum Power Dissipation at T _c = 25°C	50	W
T _J	Operating Temperature Range	-55 to 150	°C
T _{STG}	Storage Temperature Range	-55 to 150	°C

Note : 1. Surface Mounted on FR4 Board , t <=10sec

2. Pulse Test , Pulse width <= 300us , Duty Cycle <= 2%

3. Repetitive Rating , Pulse width limited by maximum junction temperature

4. Guaranteed by design , not subject to production testing

Thermal characteristics

R _{θJA}	Thermal Resistance, Junction-to-Ambient (Note 1)	50	°C/W
------------------	--	----	------

2006-02

RATING CHARACTERISTIC CURVES (CHM1012PAPT)

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
--------	-----------	------------	-----	-----	-----	-------

OFF CHARACTERISTICS

BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}} = 0 \text{ V}, I_D = 250 \mu\text{A}$	120			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{\text{DS}} = 120 \text{ V}, V_{\text{GS}} = 0 \text{ V}$			25	μA
I_{GSSF}	Gate-Body Leakage	$V_{\text{GS}} = 20 \text{ V}, V_{\text{DS}} = 0 \text{ V}$			+100	nA
I_{GSSR}	Gate-Body Leakage	$V_{\text{GS}} = -20 \text{ V}, V_{\text{DS}} = 0 \text{ V}$			-100	nA

ON CHARACTERISTICS (Note 2)

$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{DS}} = V_{\text{GS}}, I_D = 250 \mu\text{A}$	2		4	V
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=10 \text{ V}, I_D=10 \text{ A}$		100	120	$\text{m}\Omega$
g_{FS}	Forward Transconductance	$V_{\text{DS}}=10 \text{ V}, I_D = 5 \text{ A}$	3	5		S

SWITCHING CHARACTERISTICS (Note 4)

Q_g	Total Gate Charge	$V_{\text{DS}}=96 \text{ V}, I_D=10 \text{ A}$ $V_{\text{GS}}=10 \text{ V}$		47.5	57	nC
Q_{gs}	Gate-Source Charge			5		
Q_{gd}	Gate-Drain Charge			16		
t_{on}	Turn-On Time	$V_{\text{DD}}=30 \text{ V}$ $I_D=10 \text{ A}, V_{\text{GS}}=10 \text{ V}$ $R_{\text{GEN}}=51 \Omega$		40	60	nS
t_r	Rise Time			85	120	
t_{off}	Turn-Off Time			56	80	
t_f	Fall Time			35	50	

DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

I_s	Drain-Source Diode Forward Current			10	A
V_{SD}	Drain-Source Diode Forward Voltage	$I_s = 10 \text{ A}, V_{\text{GS}} = 0 \text{ V}$		0.85	V