

VGA with RS232 over Cat5/Cat6 Extender Kit, Wallplate Transmitter and Receiver, 1920x1440 at 60Hz, Up to 1000-ft.

MODEL NUMBER: **B130-101S-WP**



Description

Tripp Lite's B130-101S-WP allows you to extend a 1920 x 1440 (60Hz) Video and RS232 Serial signal up to 500 ft., or a 1024 x 768 (60Hz) Video and RS232 Serial signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's [N022-01K-GY](#) (Cat5) and [N222-01K-GY](#) (Cat6). For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite [P524-01K](#). Kit includes a Wallplate style Transmitter and Receiver. A "Y" cable is included for use at the computer to allow a local monitor to be attached. Ideal for digital signage situations, such as retail, schools, church, etc, as well as serial POS. Remote unit contains Equalization length (EQ) and Brightness (Gain) adjustment screws for crystal clear images...small screwdriver is included with the unit. Cat5e/Cat6 Solid conductor cable recommended.

Features

- Extends a 1920 x 1440 (60Hz) Video and RS232 Serial signal up to 500 ft., or a 1024 x 768 (60Hz) Video and RS232 Serial signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's [N022-01K-GY](#)(Cat5) and [N222-01K-GY](#) (Cat6)
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite [P524-01K](#)
- Connections for optional local monitor ("Y" Cable)
- Wallplate style Transmitter & Receiver for clean installation
- 110 Punchdown Tool, and Screwdriver to adjust Gain and Brightness, included
- Secure, screw down power connection on wallplates
- Works with: Monitors, Projectors, HDTV's, Flat panels, and any type of Serial Device

Specifications

Highlights

- Extends a 1920 x 1440 (60Hz) Video and RS232 Serial signal up to 500 ft., or a 1024 x 768 (60Hz) Video and RS232 Serial signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's [N022-01K-GY](#)(Cat5) and [N222-01K-GY](#) (Cat6)
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite [P524-01K](#)
- Connections for optional local monitor
- Wallplate style Transmitter & Receiver for clean installation

System Requirements

- Computer with VGA video output connector and DB9 Male RS232 output
- Monitor(s) with VGA input
- Serial device with DB9 connection

Package Includes

- Local Wallplate Unit
- Remote Wallplate Unit
- "Y" VGA cable
- DB9M to 3.5mm plug Serial cable (Remote serial connection)
- DB9F to 3.5mm plug Serial cable (Local serial connection)
- Owners Manual
- Screwdriver
- 110 Punch Down tool
- 2 x External Power Supply (5-15P Plug), Input: 100-240V, 50/60Hz, 0.4A, Output: +5V, 2A



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

RoHS	Y
OVERVIEW	
Chromebook Compatible	No
Display Style	Extender
Model Type	VGA
Cable Types	CAT5/CAT5E
CONNECTIONS	
Connector A	HD15 (FEMALE) (X2)
Connector B	3.5MM (FEMALE) (X2)
Connector C	110 (FEMALE) (X2)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.