

Product Datasheet

P/N MRG5903


Page 1 of 2

Rev. 1/ 2005-10-03

Coax cable

Min RG59

Construction & Dimensions



- | | | |
|---|-----------------|---|
| 1 | Inner conductor | Copper clad steel |
| 2 | Dielectric | Foam PE |
| 3 | Braid | Bare copper |
| 4 | Sheath | PVC according the European Standard HD 624. |

1. **Conductor** Innenleiter - Conduttore Interno - Conducteur
Diameter: 0.64 mm \pm 0.02 mm
2. **Dielectric** Dielektrikum – Dielettrico - Diélectrique
Diameter: 2.9 mm \pm 0.15 mm
- Outer Conductor** Aussenleiter - Conduttore Esterno - Conducteur extérieur
Diameter screen: 3.4 mm \pm 0.2 mm
Coverage braid: 85 % \pm 4 %
4. **Jacket** Aussenmantel – Guaina - Gaine
Diameter: 4.15 mm \pm 0.2 mm

Requirements and test methods

Electrical characteristics

Mean characteristic impedance: 75 \pm 2 Ω

Wellenwiderstand - Impedenza Caratteristica Principale - Impédance nominale

Nominal capacitance conductor to shield: 54 pF/m

Kapazitaet - Capacità Nominale Conduttore/Schermo - Capacité nominale entre conducteur et blindage

Nominal velocity of propagation: 84%

Ausbreitungsgeschwindigkeit - Velocità Nominale di Propagazione - Vitesse de propagation nominale

Nominal Attenuation: Wellendaempfung - Attenuazione Nominale - Affaiblissement

MHz	dB/100m
10	4
200	14
400	20
1000	33
2400	51

Maximum frequency: 1 GHz

Voltage rating :

DC 3.5 kVdc

RMS 2 kVrms

Mechanical and physical characteristics

Temperature range - storage/operation -30°C to +70°C

Temperature range - installation -5 °C to + 50°C

Nominal cable weight 30 kg/km

Gewicht - Peso Nominale del Cavo – Poids

Product Datasheet

P/N MRG5903

Page 2 of 2

Rev. 1/ 2005-10-03

Coax cable**Min RG59**

Ordering information

P/N	Jacket colour	length	RS P/N
MRG5903.00100	Black	100m	5218076
MRG5903.00500	Black	500m	5218082