



# Series 801 Mighty Mouse and Series 811 High Density Rubber Protective Cover

## 809-190 and 809-191 Ordering Information



**Splashproof Molded Rubber Covers** fit all Series 801 and 811 plugs and receptacles. Braided black nylon lanyard is available with metal rings, cable tie or slipknot for attachment to panel or to cable. -40° to +120° C operating temperature, fungus resistant per MIL-STD-810G Method 508.6.






How To Order	
<b>Sample Part Number</b>	<b>809-191</b> -05 G 6 -SCS 6
<b>Series (See Table I)</b>	809-191 = Plug Cover 809-190 = Receptacle Cover
<b>Shell Size</b>	5, 6, 7, 8, 9, 10, 11, 13, 16, 17, 19, 21
<b>Lanyard Type</b>	G = Nylon Rope Omit for no lanyard
<b>Attachment Length (inches)</b>	Omit for attachment Type N (No Attachment) Example: "-6" equals six inch length
<b>Attachment Type (See Table II)</b>	-WS = Nylon Cable -SCS = Adjustable Slip Knot -00 = Lanyard with No Attachment Lug Terminals = -01 thru -07 Solid Ring = -08 thru -33
<b>Material</b>	Omit for Neoprene Rubber per ASTM-D-2000 BC610Z1 C = Conductive Neoprene Blend (Conductance = 100K Ohms/Sq. Minimum)

Table I: Cover Style	
	
<b>809-190</b> Receptacle Cover	<b>809-191</b> Plug Cover

### NOTES

#### Materials and Finishes

- Cover: neoprene rubber blend, black
- Lanyard: .062" (1.57) diameter nylon cord, black
- Cable tie: 6/6 nylon, black, SST locking tab
- Ring: stainless steel, black zinc-cobalt finish
- Crimp sleeve: copper alloy, black zinc-cobalt finish

Table II: Attachment Code	
	<b>-WS</b> Nylon Cable Tie, 1.77 Inch (45mm) Maximum Wire Bundle Diameter
	<b>-SCS</b> Adjustable Slip Knot with Crimp Sleeve. The sleeve can be crimped with pliers for a permanent attachment.
	<b>-00</b> Lanyard With No Attachment (Fused End)
Lug Terminals and Rings	
	<b>-01</b> - .126 (3.20) I.D. <b>-02</b> - .140 (3.56) I.D. <b>-03</b> - .145 (3.68) I.D. <b>-04</b> - .156 (3.96) I.D. <b>-05</b> - .167 (4.24) I.D. <b>-06</b> - .188 (4.78) I.D. <b>-07</b> - .197 (5.00) I.D.
	<b>-08</b> - .385 (9.78) I.D. <b>-09</b> - .445 (11.30) I.D. <b>-11</b> - .570 (14.48) I.D. <b>-13</b> - .635 (16.13) I.D. <b>-14</b> - .695 (17.65) I.D. <b>-16</b> - .885 (22.48) I.D. <b>-19</b> - 1.070 (27.18) I.D. <b>-20</b> - 1.135 (28.83) I.D. <b>-22</b> - 1.210 (30.73) I.D. <b>-23</b> - 1.275 (32.39) I.D. <b>-26</b> - .950 (24.10) I.D. <b>-27</b> - .766 (19.50) I.D. <b>-29</b> - .315 (8.00) I.D. <b>-30</b> - 1.380 (35.10) I.D. <b>-32</b> - .265 (6.70) I.D. <b>-33</b> - .510 (13.00) I.D.



Dimensions in Inches (millimeters) are subject to change without notice.