

HB-156

15.6" High brightness open frame LCD monitor

Features

- Flexible, low cost and high brightness
- For semi-outdoor kiosk, vending machine, signage application
- 15.6" WXGA TFT LCD with LED backlight
- High brightness enhancement
- VESA mount (75x75, 100x100mm)
- Option with anti-reflective treatment



Specifications

LCD panel	Size	15.6" (16:9)
	Backlight	LED
	Panel type	TN
	Pixel pitch	0.252x0.252 mm
	Active area	344.23x193.54 mm
	Brightness *	1000 nits (max.) *
	Contrast	500 : 1
	Viewing angle	80/80/85/85 degree
	Resolution	1366 x 768
	Display color	16.7M (6 bit+HiFRC)
Video	Response time	Tr/Tf=6/2 mS
	Hor. frequency	30 ~ 76 KHz
	Ver. frequency	60/70/75 Hz
	Pixel rate	137 MHz

Signal input	VGA, DVI-I	
OSD adjustment	Power, Enter, Left, Right, Auto	
Power	DC connector	2.5mm diameter
	DC input	12 Vdc / 1.5A
	Consumption	18W
	Management	VESA DPMS
Mounting	75x75, 100x100mm VESA mount	
Dimension		
Net weight		
Package	Packing	3 pcs / carton
	Carton size	
	Container loading	
Temperature	Operation	-20 ~ 60 degree C
	Storage	-30 ~ 80 degree C

* Higher brightness is on demand.

Ordering information

■ Model selection

HB-156-XYZ	X: Panel selection	Y: Input selection	Z: Touch selection
	0: Standard, chosen	0: Standard, VGA/DVI	0: Standard, none
	A: Specified LCD	V: VGA only	G: Glass
	B: Specified LCD	H: VGA/DVI/HDMI	R: Resistive
	...etc. Specified LCD	P: DVI/HDMI/DP	C: Surface capacitive
		S: VGA/DVI/S-video	P: Projective capacitive
			I: IR
			S: SAW

■ Optional accessories

- * Power adapter 100 ~ 240 Vac adapter with 12Vdc / 3A o/p
- * Power cord 1.8M power cord, US / EU
- * Signal cable 1.8M VGA cable, 1.8M DVI cable

Product drawing