






CIRCUIT: SPDT

CONTACT CONFIGURATION

SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
DN	NONE	DN
2-1	OPEN	2-3



RECOMMEND P.C.B. LAYOUT



NOTES:

- ALL DIMENSIONS IN MM [INCH]
- GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
- TERM NOS. FOR REF. ONLY
- RATING: 5A @120VAC or 28VDC:  
2A @250VAC
- CONTACT MATERIAL:  
Copper ALloy w/Silver plate
- ELECTRICAL LIFE: 30,000 ACTUATIONS @Full Load
- INSULATION RESISTANCE: 1000 Mega Ohms min.
- DIELECTRIC STRENGTH: 1000V RMS @SEA LEVEL.
- OPERATING TEMPERATURE: -30°C TO 85°C

**E-SWITCH®**

TITLE				
500SSP1S1M7QEA				
SCALE	DATE	DR	DWG	REV
2:1	2/24/95	AR	T511012	C

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

C	14535	REVISED AND REDRAWN	11/22/04	AR
REV.	ECN No.	DESCRIPTION	DATE	CHKD