


RECOMMEND P.C.B. HOLES

▲ Hex Nut (T100000) installed loosely against shoulder as shown.



CIRCUIT: SPDT

CONTACT CONFIGURATION

| | | |
|-----|------|-----|
| DN | NONE | DN |
| 2-3 | OPEN | 2-1 |

NOTES:

- 1. ALL DIMENSIONS IN MM
- 2. TERM. NOS. FOR REF ONLY
- 3. SUPPLY WITH OTHER HARDWARE:
 - * 1ea. BLIND DRESS NUT, T100006
 - * 1ea. LOCK WASHER, T100011
- 4. MUST PASS GO-NO-GO GROUND TO TERMINALS, DWV ≥ 12KV



100 SP-1 T6 B50 M3 Q E
SPECIAL MADE W/B15 BUSHING - TELCO

| | | | |
|------|-------------------|------|------|
| D | REVISED & REDRAWN | DATE | CHKD |
| REV. | DESCRIPTION | DATE | CHKD |

| TOLERANCES | |
|------------|-------|
| 0.0 | ±0.4 |
| 0.00 | ±0.25 |

| | | | | |
|-------|---------|----|---------|-----|
| SCALE | DATE | DR | DWG | REV |
| 2:1 | 3/10/95 | MM | T111029 | D |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED