



AMERICAN MICROSEMICONDUCTOR INC.

P. O. Box 104
 Madison, New Jersey 07940 U.S.A.
<http://www.americanmicrosemi.com>
 email:sales@americanmicrosemi.com
 Phone: (973) 377-9566 Fax: (973) 377-3078

FEATURES

- 8 Diode Array
- Standard 16 pin Dual-In-Line Package

MECHANICAL


- Molded 16 Pin Dip
- Weight: 0.997 grams (approximate)
- Marking: Device number

MAXIMUM RATINGS

- Operating Temperatures: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Forward Surge Current: 2.0 Amps (8.3 mS)
- Continuous forward current I_F : 400mA
- Power dissipation (P_D): 500mW
- Derating factor: 4.0mW/°C

PACKAGING

- Carrier tube 25 pcs per (STANDARD)



ELECTRICAL CHARACTERISTICS @ 25°C Unless otherwise specified

Part Number	$V_{(BR)}$ @100 μ A	I_R +25°C		CAP @0V	trr	V_F @ $I_F=$ 10mA	V_F @ $I_F=$ 100mA
	V	MAX	μ A @ V_R	pF MAX	(nS) MAX	V MAX	V MAX
ADA1108P	MIN 50	1	40	19	8	1.0	1.2

