


Loadcenter Accessories

Loadcenter Options and Accessories (Continued)

3



GBK14



BRGBK39512

Table 3-111. Ground Bar Kits

Description (See Legend)	Length Inches (mm)	Ordering Quantity ①	Catalog Number	Price U.S. \$ Each
●○○○○○●	2.54 (64.5)	1	GBK5 ②	
●○○○○●■	3.59 (91.2)	1	GBK520 ②	
●○○○○●○○○○○	4.29 (109.0)	1	GBK10 ②	
●○○○○●○○○○○■	5.34 (135.6)	1	GBK1020 ②	
●○○○○●○○○○○●○○○○○	4.61 (117.1)	1	GBK13 ②	
●○○○○●○○○○○●○○○○○	5.69 (144.5)	1	GBK14 ②	
●○○○○●○○○○○●○○○○○■	6.74 (171.2)	1	GBK1420 ②	
●○○○○●○○○○○●○○○○○	8.14 (206.8)	1	GBK21 ②	
●○○○○●○○○○○●○○○○○■	9.19 (233.4)	1	GBK2120 ②	
■●●●●■●●●●■●●●●■	5.78 (146.8)	1	BRGBK39512 ③④	
○○○○○	1.84 (46.7)	1	GB4NM ⑤	

- ① Must be purchased in multiples of ordering quantities indicated.
- ② Distance between mounting holes is 1.75 inches (44.5 mm).
- ③ For single- and 3-phase 400 and 600 ampere applications.
- ④ Distance between mounting holes is 2.34 inches (59.5 mm).
- ⑤ For non-metallic enclosures. Snaps into molded base.

Ground Bar Legend

- (3) #14 – #10 Cu/Al or (1) #14 – #4 Cu/Al
- (1) #6 – 2/0 Cu/Al
- ▣ (1) #14 – #6 Cu/Al or (2) #14 – #12 Cu/Al
- ▢ (1) 1/8 – 14 or (3) #10 – 12 Cu/Al
- (1) #14 – 1/0 Cu/Al or (3) #14 – #10 Cu/Al
- (1) #6 – 14 Cu/Al or (2) #1/0 – 14 Cu/Al
- Mounting Hole