

American Microsemiconductor Inc.
 133 Kings Rd.
 Madison NJ 07940 U.S.A.
 Tel. 973-377-9566
 Fax: 973-377-3078
 E-mail: sales@americanmicrosemi.com
 Website: www.americanmicrosemi.com

ENCAPSULATED BRIDGES (Single Phase Types)

| TYPE No. | I _o (AV) A | V _{FM} Per Diode V | @ I _{FM} A | @ T _{amb} °C | Voltage Range | I _{FSM} A | I _T 2 2 A Sec. | T _{j max} °C | Physical Dimension Ref. Fig. |
|-----------|--------------------------|-----------------------------------|------------------------|--------------------------|------------------|-----------------------|------------------------------------|--------------------------|------------------------------------|
| 1 KAB | 1.2 | 1.1 | 1.88 | 45 | 100-1000 | 50 | 12.5 | 150 | 1 |
| 2KAB | 1.9 | 1.1 | 3.00 | 45 | 100-1000 | 50 | 12.5 | 150 | 2 |
| 3KCB | 2.7 | 1.1 | 4.25 | 45 | 100-1000 | 100 | 50.0 | 150 | 3 |
| BC2.2/3.5 | 3.5 | 1.2 | 5.50 | 40 | 100-1000 | 120 | 50.0 | 150 | 4 |
| 5 SB | 5.0 | 1.2 | 7.85 | 40 | 100-000 | 150 | 110.0 | 150 | 5 |
| 101 PB | 10.0 | 1.2 | 15.70 | 55 | 100-1200 | 300 | 450.0 | 150 | 6 |
| 26 MB | 25.0 | 1.1 | 39.30 | 65 | 100-1200 | 335 | 560.0 | 150 | 7 |
| 36 MB | 35.0 | 1.2 | 55.00 | 55 | 100-1200 | 400 | 800.0 | 1500 | 7 |