

AGF700 Series

700 Watts

Data Sheet

Total Power: 700 Watts
Input Voltage: 36 - 75 V
of Outputs: Single

SPECIAL FEATURES

- 2:1 Wide input range
- Extra wide trim range
- Optimised for high density, small space applications
- Low ripple and noise
- Fixed switching frequency
- Super high efficiency
- High capacitive load capability
- Basic insulation system
- Aluminium Substrate
- Functions
- Power good
- Auxiliary power rail
- Current share

SAFETY

- UL 60950-1
- IEC60950 -1



Electrical Specifications

Input

Input range:	36 - 75 VDC
Efficiency ² :	94.5%

Output

Voltage tolerance:	+/-1%
Line regulation:	15mV
Load regulation:	60mV
Noise/ripple:	250mV
Over voltage protection:	Hiccup
Over temperature protection:	Auto restart
Switching frequency:	320 KHz
Temperature coefficient:	±0.02/°C

Isolation

I/O isolation:	1500 VDC min.
----------------	---------------

Environmental Specifications


Operating ambient temperature range:	-40°C to +85 °C
Storage temperature:	-55 °C to +125 °C
Humidity:	5% to 95% (non-condensing)
MTBF:	1.5 Million hours
RoHS Compliant	

Ordering Information

Model number	Input voltage	Output voltage	Power
AGF700-48S30LT	36-75 Vin	30V @ 25A	700W

- Standard version is negative enable
- "-6" = 3.8mm pin length
- "-L" = RoHS6 compliance
- "-T" = Through hole fixture

Mechanical Drawings



Unit: mm[inch] Bottom view: pin on upside
 Tolerance: X.Xmm±0.5mm[X.X in.±0.02in.]
 X.XXmm±0.25mm[X.XX in.±0.01in.]

Pin length option

Device code suffix	L
-4	4.8mm ± 0.5 mm
-6	3.8mm ± 0.5mm
-8	2.8mm ± 0.5mm
None	5.8mm ± 0.5mm

Pin Designations

Pin No.	Name	Function
1	+On/Off	Remote control
2	-On/Off	Remote control
3	V_{in+}	Positive input voltage
4	V_{in-}	Negative input voltage
5,6	V_{o-}	Negative output voltage
7,8	V_{o+}	Positive output voltage
9	AUX	Auxiliary voltage
10	IOG	Inverter operation good
11	NC	
12	Trim	Trim terminal
13	+S	Remote sensing +
14	-S	Remote sensing -

Notes:

1. All specifications are subject to change without notice. Mechanical drawings are for reference only.
2. Warranty: 2 years
3. Label and logo appearance may vary from what is shown on mechanical drawings.

WORLDWIDE OFFICES

Americas

2900 S.Diablo Way
Tempe, AZ 85282
USA
+1 888 412 7832

Europe (UK)

Waterfront Business Park
Merry Hill, Dudley
West Midlands, DY5 1LX
United Kingdom
+44 (0) 1384 842 211

Asia (HK)

14/F, Lu Plaza
2 Wing Yip Street
Kwun Tong, Kowloon
Hong Kong
+852 2176 3333

ARTESYN[™]
EMBEDDED TECHNOLOGIES

www.artesyn.com

While every precaution has been taken to ensure accuracy and completeness in this literature, Artesyn Embedded Technologies assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions. Artesyn Embedded Technologies, Artesyn and the Artesyn Embedded Technologies logo are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners. © 2014 Artesyn Embedded Technologies, Inc.

For more information: www.artesyn.com/power
For support: productsupport.ep@artesyn.com