

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Line Conditioner - Automatic voltage regulation with surge protection

MODEL NUMBER: LC2400





Description

2400 watt Automatic Voltage Regulation (AVR) system. Protects sensitive electronics, computer accessories and home theater equipment from power-related damage and performance problems. Extends the useful life of connected equipment by providing optimum voltage conditions for enhanced efficiency and cooler internal operating temperatures. Reliable transformer-based voltage correction circuits maintain 120V nominal output during voltage fluctuations between 89 and 140V. Three levels of voltage stabilization offer targeted response for

Highlights

- Automatically adjusts low or high voltage
- 2400 watts continuous
- 4 NEMA 5-15R outlets; 2 NEMA 5-20R outlets
- \$25,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Applications

Maintains regulated output
 voltage during severe brownouts
 and overvoltages for computer
 accessories, printers, home
 theater equipment, a/v
 components, point-of-sale
 equipment, and other
 applications requiring clean,
 regulated AC power.

Package Includes

- LC2400 Line Conditioner
- Instruction manual

overvoltages, undervoltages and severe brownouts. Prevents equipment damage and power related performance problems for computer accessories, printers, home theater equipment, a/v components and other sensitive electronic devices. Network-grade AC surge and EMI/RFI noise suppression. Supports loads up to 2400 watts, 20A. Includes 6 AC outlets, 6 ft AC line cord and 7 diagnostic LEDs which display incoming voltage level, surge suppression status and line fault status. \$25,000 connected equipment insurance (USA and Canada Only).

Features

- Maintains usable 120V nominal output during brownouts as low as 89V and overvoltages as high as 140V
- 2,400 watts output power rating supports heavy 120V loads up to 20 amps
- Network grade surge suppression
- Complete EMI/RFI noise filtering
- 7 diagnostic LEDs indicate input voltage levels, surge suppression status and line fault conditions
- 6 protected outlets (four NEMA5-15R and two NEMA5-20R)
- 6-ft. AC power cord with standard NEMA5-15P input plug
- \$25,000 Ultimate Lifetime connected equipment insurance (USA and Canada Only)

Specifications

ОИТРИТ	
Output watts	2400





Outrot a sasia desalta as	400///0011-	
Output nominal voltage	120V / 60Hz	
Outlet quantity / type	6 (4 NEMA5-15R, 2 NEMA5-20R)	
INPUT		
Input cord length (ft.)	6	
Input cord length (m)	1.83	
UPC ASSIGNMENT		
Unit Carton UPC#	037332040060	
LEDS ALARMS & SWITCHES		
Front panel LEDs	7 LEDs show incoming voltage status, protection present and line fault conditions	
SURGE / NOISE SUPPRESSION		
UPS AC suppression joule rating	1440 joules	
EMI / RFI AC noise suppression	80 dB	
PHYSICAL		
Shipping weight (lbs)	13.00	
Shipping weight (kg)	5.90	
Unit Dimensions (HWD/in)	6.75 x 5.75 x 6.75	
Unit Dimensions (HWD/cm)	17.15 x 14.61 x 17.15	
Material of construction	Plastic	
Form factors supported	Small Tower	
WARRANTY		
Product Warranty Period (Worldwide)	2-year limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$25,000 Ultimate Lifetime Insurance	

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite: