



Fork Board Lock Type

Directive 2002/95/EC
RoHS
Compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION.

DO NOT ALTER CAD DRAWING BY HAND

CONEC CORPORATION Brampton, Ontario		tolerance <small>unless otherwise specified</small>	date	name
2004	drawn: Javed	date	name	
	appd: Robert S	date	name	
	norm: Robert S	date	name	
	rev: description	date	name	

2004	drawn: Javed	date	name
	appd: Robert S	date	name
	norm: Robert S	date	name
	rev: description	date	name

scale:	SEE NOTES
material:	
title:	D-Sub SMT 15 Female Connector
drawing no.:	AutoCAD 2004
part no.:	C0410DD03A
	33DSMT1-E15SNCT
DIN	A3
sheet	1/1

- Notes:
- Material And Finish
 - Shell: Steel, Nickel Plated
 - Bracket: Brass strip-H nickel plated
 - Screw: Brass nickel plated
 - Insulator-NYLDN 6T, UL-94V0, color black
 - PC 99: Colorful insulator
 - Pantone #661C: High Density 15 pos, Female
 - Contact: Phosphor bronze
 - Mating area: Gold plated
 - Sold Tails: Tin Plated

- Specifications
- Rated current: 5A max.
 - Rated Voltage: 300 VDC
 - Withstanding Voltage: 500 VAC (RMS) for 1 minute
 - Insulation Resistance: 1000 MΩm min. at 500 VDC
 - Contact Resistance: 13 mΩm max.
 - Dielectric Strength: 1000 VAC (RMS) for 1 minute
 - Temperature: -55 °C~+105 °C
- Operational Note:
- ①. Partmarking area to be degreased prior to marking operation

used for: