



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. RATING: 6A @250VAC;9A @125VAC (UL, CSA)  
4(1)A @250VAC (VDE, SEMEKO, NEMKO, FIMKO, DEMKO)
  4. CONTACT RESISTANCE: 20MILLIOHMS TYP. INITIAL
  5. INSULATION RESISTANCE: 1000MegaOHMS
  6. DIELECTRICAL STRENGTHS 1500V RMS min. @SEA LEVEL  
3000V RMS @SEA LEVEL
  7. MECHANICAL LIFE: 50,000 CYCLES.
  8. ELECTRICAL LIFE: 10,000 CYCLES.

PANEL THICKNESS	X
0.75-1.25 [.030-.049]	19.2 [.756]
1.25-2.0 [.049-.079]	19.4 [.764]
2.0-3.0 [.079-.118]	19.8 [.780]

**E-SWITCH®**

TITLE		SCALE		DATE		DR		DWG		REV	
R1973B BLK BLK GRD		1.5:1		9/6/01		CB		M400001		C	
REV.	ECN No.	DESCRIPTION	DATE	CHKD							
C	11634	REVISED	9/6/01	CJB							
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED											