



**NOTES:**

1. METALSHELLS: COPPER ALLOY; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0; GREEN
3. SIGNAL CONTACTS: COPPER ALLOY  
PLATING: 30µin HARD GOLD over min. 50µin NICKEL  
SOLDER CUP ACCEPTS CABLE AWG 20
4. NO CONTACTS ON POS. A1 and A2
5. UL APPROVED UNDER E228329
6. CONNECTOR IS PART MARKED: 3007W2PCM99A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND					tolerance	dim. in mm	scale: 2:1 (5:1)		
					date		name	material: SEE NOTES	
					drawn	08.05.02	Parei	title: <b>D-SUB COMBINATION MALE</b> 7W2P SOLDER CUP	
					appd.	08.05.02	E.Mickenbecker		
					norm				
	3 x c	Ä3935	15.03.2011	K.H.	d-old			dwg no:	Inventor 10
1 x b	Ä3231	19.12.2008	Lehmen			13K1A562		sh: 1	
a	Origin								
rev.	description	date	name			part no:		3007W2PCM99A10X	