



Description

Grounding kits protect base station systems against lighting strikes. Fits coax cables from 1/2"to 3", also fits elliptical waveguide EW43 to EW220 and WE61 to WE191.

Part number

SLGK002C-CXX-XXX

XXX indicates the grounding cable length (cm)

*The length XXX in the table is recommended length, can be changed according to customer's request.

Parts list

Piece parts

- Grounding strap
- Grounding cable BVR 16mm²
- Single-hole lug(Width 13.5mm)
- Bolt M8
- flat washers
- Nut M8
- spring washers
- Rivet M6.2*6mm
- Sealing

Materials

- Copper
- Copper(Conductor)
- PVC (Jacket), Black, BV
- T2, Tin-plated
- Stainless steel SUS304
- Stainless steel SUS304
- Stainless steel SUS304
- Stainless steel SUS304
- Brass
- 3M 2166 Butyl rubber tape (63.5mm×0.6m)
- 3M 1712 Insulated tape(50mm×10m)

Electrical data

- Contact resistance ≤ 2.5mΩ
- Maximum current handling ≥100kA, 8/20us

Environmental data

- Temperature range -40°C to +70°C
- 2002/95/EC (RoHS) Compliant

Packing

- Standard 1pce in plastic bag
- Weight Upon the length of grounding cable

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Checker	Approved	Date	Rev.	Engineering change number	Name	Date
Alex	25/11/2013	Sky	Lucy	25/11/2013	a00	15-s001	Alex	15/02/2015

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany Tel. : +49 8684 18-0 Fax : +49 8684 18-499 www.rosenberger.de Email : info@rosenberger.de					Rosenberger Asia Pacific Electronic Co., Ltd., China Tianzhu Airport Industrial Zone, Beijing, China Tel.: +86 10 80481995 Fax: +86 10 80497052 www.rosenbergerap.com Email: info@rosenbergerap.com			Page 1 / 1
--	--	--	--	--	---	--	--	---------------