

KEMET Part Number: PHE845VZ6470MR30L2
(F845FV474M760ALW0L, PHE845VZ6470MF16R30L2)



Film, Metallized Polypropylene, Safety, PHE845/F845, 0.47 uF, 20%, 1,500 V, 760 V, 105C, Lead Spacing = 27.5mm



Dimensions	
L	31.5mm MAX
H	30mm MAX
T	21mm MAX
S	27.5mm +/-0.4mm
LL	30mm -1mm
F	0.8mm NOM

Packaging Specifications	
Packaging:	Bulk, Tray
Packaging Quantity:	108

General Information	
Dielectric:	Metallized Polypropylene
Style:	Radial
Series:	PHE845/F845
Features:	Pulse
RoHS:	Yes
Lead:	Wire Leads
Approvals:	ENEC, UL, cUL

Specifications	
Capacitance:	0.47 uF
Capacitance Tolerance:	20%
Voltage DC:	1500 VDC
Voltage AC:	760 VAC
Temperature Range:	-40/+105C
Rated Temperature:	105C
Dissipation Factor:	0.1% 1kHz, 0.4% 10kHz
Insulation Resistance:	21.2766 GOhms
Max dVdt:	100 V
Safety Class:	X1

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2017 IntelliData.net