

# SIDE LOOK PACKAGE SOLID STATE LAMP

## MSL-854SG

### Description

The MSL-854SG is designed based on an industry standard package for ease of handling and use. The package is water clear epoxy within white plastic.

### Package Dimensions


Units : mm

### Applications


- LCD backlighting
- Symbol backlighting
- Front panel indicator

### Features

- High performance
- Excellent chip to chip consistency
- High reliability



ANODE                      CATHODE



Notes :

1. All dimensions are in millimeters.
2. Tolerance is  $\pm 0.25$  mm unless otherwise

### Absolute Maximum Ratings

@  $T_A=25^\circ\text{C}$

Parameter	Symbol	Maximum Rating	Unit
Power Dissipation	$P_{ad}$	200	mW
Continuous Forward Current	$I_{af}$	25	mA
Reverse Current( $V_R=5V$ )	$I_R$	10	$\mu\text{A}$
Operating Temperature Range	$T_{opr}$	$-40^\circ\text{C}$ to $+85^\circ\text{C}$	
Storage Temperature Range	$T_{stg}$	$-40^\circ\text{C}$ to $+85^\circ\text{C}$	
Lead Soldering Temperature $260^\circ\text{C}$ for 5 second (2.0mm From Body)			

**UNI**

Unity Opto Technology Co., Ltd.

11/6/2000

## Optical-Electrical Characteristics

@ T<sub>A</sub>=25°C

PART NO	Color		Peak Wave Length $\lambda_D$ (nm)	Spectral Halfwidth $\Delta\lambda$ (nm)	Forward Voltage @ I <sub>F</sub> =20mA (V)		Luminous Intensity @ I <sub>F</sub> =20mA (mcd)		Viewing Angle 2θ <sub>1/2</sub> (deg)
	Emitted	Lens			TYP	MAX	MIN	TYP	
MSL-854SG	Signal Green	Water Clear	505	30	7.0	8.0	350	520	110

### Typical Optical-Electrical Characteristic Curves




FIG.1 RELATIVE LUMINOUS INTENSITY VS. WAVELENGTH




FIG.2 FORWARD CURRENT VS.FORWARD VOLTAGE




FIG.3 FORWARD CURRENT VS. AMBIENT TEMPERATURE




FIG.4 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




FIG.5 RADIATION PATTERN DIAGRAM