


# NA130 NEW

Desktop Network Appliance Platform with AMD G-Series LX Family GX-210 Processor and 4 LANs

## Features

- AMD G-Series LX processor
- One DDR3L-1600 SO-DIMM, up to 8GB memory
- Four 10/100/1000 Mbps Ethernet ports (Realtek 8111G)
- Wi-Fi module through PCI Express Mini Card for optional
- Suitable for VPN, network bandwidth controller and firewall applications



## Specifications

System	
CPU	AMD G-Series LX family GX-210 processor
Chipset	SoC Integrated
Memory	1 x DDR3L-1600 SO-DIMM max. up to 8GB non-ECC memory
BIOS	AMI SPI Flash BIOS
Storage	1 x 2.5" SATA HDD 1 x mSATA
Network Interface	4 x 10/100/1000 Mbps Ethernet (Realtek 8111G, optional 6 ports by request)
I/O Interface	1 x RS-232 (RJ-type) 1 x USB 2.0 1 x USB 3.0 4 x RJ-45
Other Features	LAN Bypass function through latch relay (one pair) for optional
Expansion Slot	1 x PCI Express Mini Card (USB interface)
Watchdog Timer	255 levels for system reset 7 levels for LAN Bypass (optional)
Power Supply	1 x 12V, 5A power adapter
OS Compatibility	Win7, Win10, Cent OS, Ubuntu, FreeBSD

## Mechanical/ Environmental

Form Factor	1U desktop
LED	Power, HDD, GPIO programmable, LAN Bypass, Link/Act with transfer rate
Operating Temp.	0°C ~ +40°C (+32°F ~ +104°F)
Humidity	10% ~ 95% RH, non-condensing
Chassis Material	Steel
Dimensions	44 mm (1.73") (H) x 231.9 mm (9.00") (W) x 152 mm (5.98") (D)
Weight (net/gross)	2.35 kg (5.18 lb)/2.61 kg (5.75 lb)
Certificates	FCC class B/CE class B

## Ordering Information

Standard	
NA130-D4GI-US (P/N: E26E130100)	1U desktop network appliance with AMD G-series LX family GX-210 processor and 4 GbE LANs

Optional	
5916E552000E	DB9F-RJ-45 1.8M console cable

\* Specifications and certifications may vary contingent on options.

## Packing List

1 x DC power adapter 12V/5A
1 x Power cord
1 x SATA cable

## Dimensions

