


PNP Transistors

KTA2015

■ Features

- Excellent hFE Linearity
- Complementary to KTC4076

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Collector - Base Voltage	V_{CB0}	-35	V
Collector - Emitter Voltage	V_{CE0}	-30	
Emitter - Base Voltage	V_{EB0}	-5	
Collector Current - Continuous	I_C	-500	mA
Base Current	I_B	-50	
Collector Power Dissipation	P_C	100	mW
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature range	T_{stg}	-55 to 150	

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector- base breakdown voltage	V_{CB0}	$I_C = -100\text{ }\mu\text{A}$, $I_E = 0$	-35			V
Collector- emitter breakdown voltage	V_{CE0}	$I_C = -1\text{ mA}$, $I_B = 0$	-30			
Emitter - base breakdown voltage	V_{EB0}	$I_E = -100\text{ }\mu\text{A}$, $I_C = 0$	-5			
Collector-base cut-off current	I_{CBO}	$V_{CB} = -35\text{ V}$, $I_E = 0$			-0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB} = -5\text{ V}$, $I_C = 0$			-0.1	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -100\text{ mA}$, $I_B = -10\text{ mA}$			-0.25	V
Base - emitter saturation voltage	$V_{BE(sat)}$	$I_C = -100\text{ mA}$, $I_B = -10\text{ mA}$			-1.2	
Base - emitter voltage	V_{BE}	$V_{CE} = -1\text{ V}$, $I_C = -100\text{ mA}$			-1	
DC current gain	h_{FE}	$V_{CE} = -1\text{ V}$, $I_C = -100\text{ mA}$	70		240	
		$V_{CE} = -1\text{ V}$, $I_C = -400\text{ mA}$	25			
			40			
Collector output capacitance	C_{ob}	$V_{CB} = -6\text{ V}$, $f = 1\text{ MHz}$		13		pF
Transition frequency	f_T	$V_{CE} = -10\text{ V}$, $I_C = -20\text{ mA}$		200		MHz

■ Classification of $h_{FE}(1)$

Type	KTA2015-O	KTA2015-Y
Range	70- 140	120-240
Mark'ng	ZO	ZY

PNP Transistors

KTA2015

■ Typical Characteristics

