

# SR120 THRU SR1200



1.0 AMP SCHOTTKY BARRIER RECTIFIERS



## FEATURES

- \* Low forward voltage drop
- \* High current capability
- \* High reliability
- \* High surge current capability
- \* Epitaxial construction

## MECHANICAL DATA


- \* Case: Molded plastic
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Lead: Axial leads, solderable per MIL-STD-202, method 208 guaranteed
- \* Polarity: Color band denotes cathode end
- \* Mounting position: Any
- \* Weight: 0.34 grams
- \* Both normal and Pb free product are available:
- \* Normal: 80~95%Sn, 5~20%Pb
- \* Pb free: 99 Sn above can meet Rohs environment substance directive request

## VOLTAGE RANGE

20 to 200 Volts

## CURRENT

1.0 Ampere



## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating 25°C ambient temperature unless otherwise specified.  
Single phase half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

| TYPE NUMBER  | SR120      | SR140 | SR160      | SR180 | SR1100 | SR1150 | SR1200 | UNITS |
|--|------------|-------|------------|-------|--------|--------|--------|-------|
| Maximum Recurrent Peak Reverse Voltage   | 20         | 40    | 60         | 80    | 100    | 150    | 200    | V     |
| Maximum RMS Voltage  | 14         | 28    | 42         | 56    | 70     | 105    | 140    | V     |
| Maximum DC Blocking Voltage  | 20         | 40    | 60         | 80    | 100    | 150    | 200    | V     |
| Maximum Average Forward Rectified Current  |            |       |            |       |        |        |        | A     |
| See Fig. 1   | 1.0        |       |            |       |        |        |        | A     |
| Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method) | 30         |       |            |       |        |        |        | A     |
| Maximum Instantaneous Forward Voltage at 1.0A  | 0.55       | 0.70  | 0.85       |       |        |        | V      |       |
| Maximum DC Reverse Current Ta=25°C   | 500        |       |            |       |        |        |        | µA    |
| at Rated DC Blocking Voltage Ta=100°C  | 10         |       |            |       |        |        |        | mA    |
| Typical Junction Capacitance (Note1)   | 110        |       |            |       |        |        |        | pF    |
| Typical Thermal Resistance RθJA (Note 2)   | 50         |       |            |       |        |        |        | °C/W  |
| Operating Temperature Range Tj   | -65 — +125 |       | -65 — +150 |       |        |        | °C     |       |
| Storage Temperature Range Tstg   | -65 — +150 |       |            |       |        |        |        | °C    |

### NOTES:

1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
2. Thermal Resistance Junction to Ambient Vertical PC Board Mounting 0.5"(12.7mm) Lead Length.

## RATING AND CHARACTERISTIC CURVES (SR120 THRU SR1200)

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL FORWARD CHARACTERISTICS




FIG.3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.4-TYPICAL JUNCTION CAPACITANCE




FIG.5 - TYPICAL REVERSE CHARACTERISTICS

