## CGA4J3X7R1C475M125AB



### TDK item description CGA4J3X7R1C475MT\*\*\*\*

Applications	Automotive Grade	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
Feature	General General (Up to 50V) AEC-Q200 AEC-Q200	
Series	CGA4(2012) [EIA 0805]	Le G
Status	Production	Dimensions

	Size
Length(L)	2.00mm ±0.20mm
Width(W)	1.25mm ±0.20mm
Thickness(T)	1.25mm ±0.20mm
Terminal Width(B)	0.20mm Min.
Terminal Spacing(G)	0.50mm Min.
Recommended Land Pattern (PA)	1.00mm to 1.30mm(Flow Soldering)
	0.90mm to 1.20mm(Reflow Soldering)
Recommended Land Pattern (PB)	1.00mm to 1.20mm(Flow Soldering)
	0.70mm to 0.90mm(Reflow Soldering)
Recommended Land Pattern (PC)	0.80mm to 1.10mm(Flow Soldering)
	0.90mm to 1.20mm(Reflow Soldering)

	Electrical Characteristics	
Capacitance	4.7µF ±20%	
Rated Voltage	16VDC	
Temperature Characteristic	X7R(±15%)	
Dissipation Factor (Max.)	7.5%	
Insulation Resistance (Min.)	21ΜΩ	

	Other	
Coldering Method	Wave (Flow)	
Soldering Method	Reflow	
AEC-Q200	Yes	
Packing	Blister (Plastic)Taping [180mm Reel]	
Package Quantity	2000pcs	


! Images are for reference only and show exemplary products.

! This PDF document was created based on the data listed on the TDK Corporation website.


! All specifications are subject to change without notice.

## CGA4J3X7R1C475M125AB







# Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)





#### CGA4J3X7R1C475M125AB

Capacitance(Nom.)/F









! Images are for reference only and show exemplary products.


! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.

# CGA4J3X7R1C475M125AB



# Associated Images



! Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.