


Data Sheet

Features




- Usable bandwidth of 4.5 MHz
- Typical 3 dB bandwidth of 4.9 MHz
- Low loss
- High attenuation
- Single-ended operation, 50Ω
- Ceramic Surface Mount Package (SMP)
- Hermetic



Package Pin Configuration

Surface Mount 13.30 x 6.50 x 1.75 mm

Bottom View



| Pin No. | Description |
|----------|-------------|
| 5 | Output |
| 11 | Input |
| 6,12 | Ground |
| 1,2,3,4 | Case Ground |
| 7,8,9,10 | Case Ground |

Dimensions shown are nominal in millimeters
 All tolerances are ±0.15mm except overall
 length and width ±0.10mm

Body: Al_2O_3 ceramic
 Lid: Kovar, Ni plated
 Terminations: Au plating 0.5 - 1.0μm,
 over a 2 - 6μm Ni plating

Data Sheet
Electrical Specifications ⁽¹⁾

 Operating Temperature: ⁽²⁾ +25 °C


| Parameter | Minimum | Typical | Maximum | Unit |
|--|---------|---------|---------|--------|
| Center Frequency | 69.85 | 70 | 70.15 | MHz |
| Insertion Loss at F _o | - | 6.8 | 7.5 | dB |
| 1 dB Bandwidth | 3.8 | 4.2 | - | MHz |
| 3 dB Bandwidth | 4.5 | 4.9 | - | MHz |
| 35 dB Bandwidth | - | 8.5 | 9.75 | MHz |
| Passband Ripple 68.425 - 71.575 MHz | - | 0.6 | 1 | dB |
| Phase Linearity 68.425 - 71.575 MHz | - | 4.5 | 6.5 | deg |
| Group Delay Variation 68.425 - 71.575 MHz | - | 115 | 180 | nsec |
| Absolute Delay | - | 0.95 | - | μsec |
| Temperature Coefficient | - | -94 | - | ppm/°C |
| Source Impedance ⁽³⁾ | - | 50 | - | Ω |
| Load Impedance ⁽³⁾ | - | 50 | - | Ω |

Notes:

1. All specifications are based on the test circuit shown below
2. All specifications are tested at room temperature only
3. This is the optimum impedance in order to achieve the performance shown





Test Circuit:

Actual matching values may vary due to PCB layout and parasitics




Data Sheet


Typical Performance (at +25°C)



Input Smith Chart




Output Smith Chart



Data Sheet



Matching Schematics

Actual matching values may vary due to PCB layout and parasitics



Marking



PCB Footprint



The date code consists of: day of the current year (Julian, 3 digits), last digit of the year (1 digit) and hour (2 digits)

This footprint represents a recommendation only
Dimensions shown are nominal in millimeters

Tape and Reel



Dimensions shown are nominal in millimeters
Packaging quantity: 2000 units/reel

Data Sheet

Maximum Ratings

| Parameter | Symbol | Minimum | Maximum | Unit |
|---------------------------|------------------|---------|---------|------|
| Storage Temperature Range | T _{stg} | -40 | +85 | ° C |

Warnings

- Electrostatic Sensitive Device (ESD)
- Avoid ultrasonic exposure



Material Content

- Does not contain lead (Pb) or other RoHS restricted materials

Links to Additional Technical Information

[PCB Layout Tips](#)

[Qualification Flowchart](#)

[Soldering Profile](#)

[S-Parameters](#)

[Other Technical Information](#)

Sawtek's liability is limited only to the Surface Acoustic Wave (SAW) component(s) described in this data sheet. Sawtek does not accept any liability for applications, processes, circuits or assemblies which are implemented using any Sawtek component described in this data sheet.

Contact Information



PO Box 609501
Orlando, FL 32860-9501
USA

Phone: +1 (407) 886-8860
Fax: +1 (407) 886-7061
Email: custservice@sawtek.com
Web: www.sawtek.com

Or contact one of our worldwide
Network of [sales offices](#),
[Representatives or distributors](#)