
# **AX61120TP**

# 1U Rackmount Chassis for full-size SBC


# **Features**

- PICMG 1.3 SBC structure with 2 expansion slots
- Internal two 3.5" HDD drive bays
- Slim-line CD-ROM disk bay for ease of system installation
- Special cooling system design for supporting Intel<sup>®</sup> Pentium<sup>®</sup>
   4 processor
- ATX 270W power supply (with PFC) for Intel® Pentium® 4 SBCs





▲ Built-in a butterfly backplane with 2 expansion slots





▲ Rear view

# **Specifications**

Standard Color	Black
Construction	Heavy-duty steel
Drive Capacity	Exposed 1 x slim-line CD-ROM Internal 2 x 3.5" HDD drive bay
Cooling	3 x 4 cm ball bearing fan
Front Panel Indicators	1 x power on/off, 1 x HDD
Front Panel Controls	1 x power on/off and 1 x system reset
Front Panel Connectors	2 x USB, 1 x PS/2 6-pin
Pre-punched Panel	Rear 1 x 9-pin, 1 x 25-pin
System Board	Full-size SBCs

Expansion Interface	2 x PCI card (half-size)
Operating Temperature	0°C ~ +40°C (+32°F ~ +104°F)
Dimensions	482.6 mm (19") (W) x 500 mm (19.7") (D) x 44.3 mm (1.75") (H)
Weight (net/gross)	9.8 kg (21.6 lb)/10.5 kg (23.15 lb)

# **Power Supply Specifications**

Items	Watt	Input	Specifications Output	MTBF
PS270-1U	ATX 270W (PFC)	AC 90~264V (Auto)	+5V @ 18A +12V 1 @ 16A +12V 2 @ 10A +3.3V @ 16A -12V @ 0.8A +5VSB @ 2.5A	100,000 hours
PS200-1U	ATX 200W (PFC)	AC 90~264V (Auto)	+5V @ 17A +12V 1 @ 6A +12V 2 @ 12A +3.3V @ 14A -12V @ 0.8A +5VSB @ 2A	100,000 hours

# **Ordering Information**

	With ATX 200W power supply	
AX61120TP/X270 With ATX 270W power supply		

<sup>\*</sup>Specifications and certifications are based on options and may vary.

#### **Recommended SBC Selections**

SBC81203 series w/ LGA775 heatsink
SBC81205 series w/ LGA775 heatsink
SBC81206 series w/ LGA775 heatsink
SBC81206 series w/ LGA775 heatsink
SHB100 series w/ LGA775 heatsink (manufacture option)
SHB103 w/ LGA1156 heatsink (manufacture option)
SHB110 series w/ LGA775 heatsink (manufacture option)
SHB106 series w/ LGA1156 heatsink (manufacture option)
SHB120 series w/ LGA1155 heatsink (manufacture option)
SHB130 series w/ LGA1150 heatsink (manufacture option)

#### **Backplane Options**

#### PICMG 1.0

Models	Slots per Segment (ISA/PCI/PCIe/CPU)	Segment
ATX6022/3VP2	0/2/0/1	Single

### PICMG 1.3

Models	Slots per Segment (ISA/PCI/PCIe/CPU)	Segment
FAB102	0/0/1/1	Single
FAB209	0/0/2/1	Single

## **Dimensions**

