


TYPE: _____ QUANTITY: _____ PROJECT: _____

CATALOG NUMBER:

FIXTURE WATTAGE VOLTAGE FINISH OPTION OPTION OPTION OPTION



- 1- Ø 3" (75) high impact white translucent acrylic diffuser UV stabilized. Available in two acrylic lengths.
- 2- Ø 3" (75) extruded aluminum base.
- 3- One piece cast aluminum base cover.

CL313/CL323/CL313XL



MATERIALS

LumiSTIK bollard is made of corrosion resistant 356 aluminum alloy with a copper (CU) content of less than 0.1%. LED is contained in a white UV stabilized high impact acrylic sealed cylinder. The assembly is designed to provide a uniform column illumination.

ELECTRICAL

DRIVER Standard driver is 0-10V dimming-ready (dims to 10%) with: 120-277 multi-volt compatibility (50-60Hz), operating temperature range of -30°C/-22°F to 60°C/140°F, output over voltage protection, output over current protection and output short circuit protection with auto-recovery.

LED Standard 4000K CCT/80 CRI. Optional 3000K and 3500K. Removable modular LED platform.

LIFE

50,000hrs $L_{85}B_{50}$ (based on IESNA TM-21 Test Method and LM-80 data).

FINISH



Five-stage preparation process includes preheating of cast aluminum parts for air extraction. Polyester powder coating is applied through an electrostatic process, and oven cured for long term finish.

CERTIFICATION

Tested to UL1598 and CSA 22.2 #250. ETL listed wet location. Photometric testing performed by an independent laboratory in accordance with IES LM-79-08 standards at 25°C. Lumen depreciation in accordance with IESNA LM80 standards. CE certification on request. Rated IP65.

MOUNTING

Mounts with a set of 3 x 3/8" -16 x 3 3/4" lg galvanized anchor bolts.



CL313/CL313XL/CL323 SERIES LumiSTIK - LED

TYPICAL PHOTOMETRY SUMMARY

Please visit our web site www.luminis.com for complete I.E.S. formatted download data.

LUMINAIRE SELECTION

MODEL	LED LIGHT SELECTION (4000K/80CRI)	VOLTAGE ¹	FINISH									
<p><input type="checkbox"/> CL313 <input type="checkbox"/> CL313XL <input type="checkbox"/> CL323</p>	<table border="1"> <thead> <tr> <th>SUFFIX</th> <th>INPUT WATTS</th> <th>DELIVERED LUMENS</th> </tr> </thead> <tbody> <tr> <td>CL313 <input type="checkbox"/> L56W10</td> <td>10W</td> <td>830</td> </tr> </tbody> </table>	SUFFIX	INPUT WATTS	DELIVERED LUMENS	CL313 <input type="checkbox"/> L56W10	10W	830	<input type="checkbox"/> 120V <input type="checkbox"/> 277V	STANDARD COLORS <input type="checkbox"/> WHT Snow white <input type="checkbox"/> BKT Jet black <input type="checkbox"/> BZT Bronze <input type="checkbox"/> MST Matte silver <input type="checkbox"/> GRT Titanium gray <input type="checkbox"/> DGT Gun metal <input type="checkbox"/> CHT Champagne <input type="checkbox"/> SGT Steel Gray <input type="checkbox"/> BGT English Cream OPTIONAL COLORS Wood grain finishes <input type="checkbox"/> NMR Mahogany red ² <input type="checkbox"/> NMO Maple oak ² <input type="checkbox"/> NTW Teak wood ² Base column only <input type="checkbox"/> CS Custom color <input type="checkbox"/> RAL RAL# color <input type="checkbox"/> SS3 #316 stainless steel body (Refer to color chart)			
	SUFFIX	INPUT WATTS	DELIVERED LUMENS									
	CL313 <input type="checkbox"/> L56W10	10W	830									
	<table border="1"> <tbody> <tr> <td>CL313XL <input type="checkbox"/> L56W10</td> <td>10W</td> <td>830</td> </tr> <tr> <td><input type="checkbox"/> L56W15</td> <td>15W</td> <td>1230</td> </tr> </tbody> </table>	CL313XL <input type="checkbox"/> L56W10	10W	830	<input type="checkbox"/> L56W15	15W	1230					
	CL313XL <input type="checkbox"/> L56W10	10W	830									
	<input type="checkbox"/> L56W15	15W	1230									
	<table border="1"> <tbody> <tr> <td>CL323 <input type="checkbox"/> L112W10</td> <td>10W</td> <td>830</td> </tr> <tr> <td><input type="checkbox"/> L112W20</td> <td>20W</td> <td>1640</td> </tr> <tr> <td><input type="checkbox"/> L112W30</td> <td>30W</td> <td>2250</td> </tr> </tbody> </table>	CL323 <input type="checkbox"/> L112W10	10W	830	<input type="checkbox"/> L112W20	20W	1640			<input type="checkbox"/> L112W30	30W	2250
	CL323 <input type="checkbox"/> L112W10	10W	830									
	<input type="checkbox"/> L112W20	20W	1640									
<input type="checkbox"/> L112W30	30W	2250										

OPTIONS

ELECTRICAL

- REML2-50** Remote mount battery backup for LED 90 mins, 7W
Remote mount to 50ft. 12" square enclosure with access cover
- FS** Fuse
- PH** Photocell
- SP** Surge protector 10KV

MOUNTING

Alternate CCT °K LED (LCF: Lumen conversion factor)

- K3** 3000K CCT 80 CRI (LCF: 0.94)
- K35** 3500K CCT 80 CRI (LCF: 0.983)

NOTE: Other CCT & higher CRI available, please consult factory.

NOTES

- 1- If no voltage is specified, luminaires are factory prewired by default for 120V. For other voltages, please specify with catalog number, or consult factory.
- 2- Cast aluminum top & base covers are as follows for selected wood grain finishes: BZT paired with NMR; SGT paired with NMO; BGT paired with NTW (Other colors available. Please contact factory).

LUMINIS®

LUMINIS | Toll free: 866.586.4647 Fax: 514.683.8872
260 Labrosse, Pointe-Claire (QC) Canada H9R 5L5

LUMINIS.COM

Luminaires may be altered for design improvement or discontinued without prior notice.