

### MLZ2012N220LT000









Applications	Commercial Grade	
Feature	Shield Magnetic Shield  Multilayer Multilayer  Ferrite Core	
Series   Type	MLZ	
Status	Production	
Brand	TDK	



	Size	
Length(L)	2.00mm ±0.20mm	
Width(W)	1.25mm ±0.20mm	
Thickness(T)	1.25mm ±0.20mm	
Recommended Land Pattern (A)	0.80mm Nom.	
Recommended Land Pattern (B)	1.00mm Nom.	
Recommended Land Pattern (C)	1.20mm Nom.	

Electrical Characteristics			
Inductance	$22\mu H$ $\pm 20\%$ at $2MHz$		
Rated Current (L Change) [Typ.]			
Rated Current (L Change) [Max.]	70mA (50% Down)		
Rated Current (Temperature Rise) [Typ.]	300mA (20°C Rise)		
Rated Current (Temperature Rise) [Max.]	70mA (20°C Rise)		
DC Resistance [Typ.]	670mΩ		
DC Resistance [Max.]	871mΩ		
Self Resonant Frequency [Min.]			
Self Resonant Frequency [Typ.]			
Q [Min.]			
Q [Typ.]			

Ot	her
Operating Temp. Range (Including Self-Temp. Rise)	-55 to 125°C
	Wave (Flow)
Soldering Method	Reflow
	Iron Soldering
AEC-Q200	No
Packing	Blister (Plastic)Taping [180mm Reel]
Package Quantity	2000pcs
What are for reference only and show exemplary products.  I This PDF document was created based on the data listed on the TDK Corporation website.	0.014g

#### MLZ2012N220LT000














## Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)











<sup>!</sup> Images are for reference only and show exemplary products.

<sup>!</sup> This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.

#### MLZ2012N220LT000










# **Associated Images**



<sup>!</sup> Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.