


MODEL BCN31


BCN31 Series

- R/2R Ladder Network
- 8 Bit, 2512 Size
- Thick Film
- Leadless Chip Packages

Features

- 8 bit ladder network in a 10 terminal leadless chip package
- Convex termination with square edges and corners
- Topside marking for easy identification
- Solder plated termination with nickel barrier



 All parts are Pb-free and comply with EU Directive 2011/65/EU (RoHS2)

Benefits

- Saves board space
- Reduces cost
- Single component reliability
- Leadless package offers improved performance

Applications

- Termination network in analog to digital and digital to analog conversion circuits

Electrical ¹

Standard Resistance Range, Ohms	1K to 100K
Standard Resistance Tolerance	±2%
Operating Temperature Range	-40°C to +125°C
Temperature Coefficient of Resistance	±100ppm/°C
Operating Voltage, Maximum	50Vdc or \sqrt{pr}
Insulation Resistance	100 Megohms
Power Rating, Watts at 70°C	25mW per Resistor / 400mW per Package
Ladder Network Accuracy	8 Bits: ±1/2LSB

General Note


TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

BCN31 Series


Environmental

Moisture Resistance	1,000 hours at +40°C, 95% R.H. (3.0% ΔR)
High Temperature Operation	1,000 hours at 70°C (3.0% ΔR)
Short Time Overload	2.5 x rated voltage, 5 seconds (2.0% ΔR)
Temperature Cycling	-55°C to +125°C, 5 cycles (1.0% ΔR)
Resistance to Solder Heat	260°C for 10 seconds (1.0% ΔR)
Load Life	1,000 hours at 70°C (3.0% ΔR)

Schematic



Solder Pad Layout (Inch/mm)




P	Wave Solder Process					Re-Flow Solder Process				
	A	B	C	X	Y	A	B	C	X	Y
.050	.084	.148	.014	.036	.032	.084	.148	.014	.036	.032
1.27	2.10	3.70	0.35	0.90	0.80	2.10	3.70	0.35	0.90	0.80

General Note


TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

BCN31 Series

Outline Dimensions (Inch/mm)




Power Derating Curve



Standard Resistance Values, Ohms

Value (R1/R2)	1K/2K	10K/20K	25K/50K	50K/100K	100K/200K
Code	102	103	253	503	104

Ordering Information



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.