

isc N-Channel MOSFET Transistor

IRFP4004, IIRFP4004

• FEATURES

- Static drain-source on-resistance:
 $R_{DS(on)} \leq 1.7m\Omega$
- Enhancement mode:
 $V_{th} = 2.0$ to $4.0V$ ($V_{DS}=V_{GS}$, $I_D=250 \mu A$)
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

• DESCRIPTION



- High Efficiency Synchronous Rectification in SMPS
- Uninterruptible Power Supply
- High Speed Power Switching

• ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ C$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{DSS}	Drain-Source Voltage	40	V
V_{GS}	Gate-Source Voltage	± 20	V
I_D	Drain Current-Continuous	195	A
I_{DM}	Drain Current-Single Pulsed	1390	A
P_D	Total Dissipation @ $T_c=25^\circ C$	380	W
T_j	Max. Operating Junction Temperature	175	$^\circ C$
T_{stg}	Storage Temperature	-55~175	$^\circ C$

• THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th(j-c)}$	Channel-to-case thermal resistance	0.4	$^\circ C/W$
$R_{th(j-a)}$	Channel-to-ambient thermal resistance	40	$^\circ C/W$



DIM	mm	
	MIN	MAX
A	19.80	20.20
B	15.40	15.80
C	4.90	5.10
D	0.90	1.10
E	1.40	1.60
F	1.90	2.10
G	10.80	11.00
H	2.40	2.60
J	0.50	0.70
K	19.50	20.50
P	3.90	4.10
Q	3.30	3.50
U	5.20	5.40
V	2.90	3.10

isc N-Channel MOSFET Transistor
IRFP4004, IIRFP4004
ELECTRICAL CHARACTERISTICS

 T_C=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V; I _D =250 μ A	40			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} ; I _D =250 μ A	2.0		4.0	V
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} =10V; I _D =195A			1.7	mΩ
I _{GSS}	Gate-Source Leakage Current	V _{GS} = ±20V			±0.2	μ A
I _{DSS}	Drain-Source Leakage Current	V _{DS} =40V; V _{GS} = 0V			20	μ A
V _{SD}	Diode forward voltage	I _S =195A, V _{GS} = 0V			1.3	V