
## KEMET Part Number: PHE845VF6220MR30L2

(F845FK224M760ALW0L, PHE845VF6220MF03R30L2)



Film, Metallized Polypropylene, Safety, PHE845/F845, 0.22 uF, 20%, 1,500 V, 760 V, 105C, Lead Spacing = 27.5mm



Dimensions		
L	31.5mm MAX	
Н	23mm MAX	
Т	13.5mm MAX	
S	27.5mm +/-0.4mm	
LL	30mm -1mm	
F	0.8mm NOM	

Packaging Specifications	
Packaging:	Bulk, Tray
Packaging Quantity:	171

General Information		
Dielectric:	Metallized Polypropylene	
Style:	Radial	
Series:	PHE845/F845	
Features:	Pulse	
RoHS:	Yes	
Lead:	Wire Leads	
Approvals:	ENEC, UL, cUL	

Specifications		
Capacitance:	0.22 uF	
Capacitance Tolerance:	20%	
Voltage DC:	1500 VDC	
Voltage AC:	760 VAC	
Temperature Range:	-40/+105C	
Rated Temperature:	105C	
Dissipation Factor:	0.1% 1kHz, 0.4% 10kHz	
Insulation Resistance:	30 GOhms	
Max dVdt:	100 V	
Safety Class:	X1	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

