#### CMXTVS5-4

#### SURFACE MOUNT SILICON LOW CAPACITANCE QUAD TVS/DIODE ARRAY



**SOT-26 CASE** 

- USB 2.0 Power and Data Line Protection
- HDMI Interface

**APPLICATIONS:** 

- Digital Video Interface (DVI)
- Ethernet Ports

## **MAXIMUM RATINGS:** $(T_A=25^{\circ}C)$ Input Voltage

ESD Voltage (IEC 61000-4-2, Air)
ESD Voltage (IEC 61000-4-2, Contact)

Operating and Storage Junction Temperature

# Central Semiconductor Corp.

www.centralsemi.com

#### **DESCRIPTION:**

The CENTRAL SEMICONDUCTOR CMXTVS5-4 is a 4-line TVS/Diode array packaged in a surface mount case. This device, with its low capacitance, was designed to protect four high speed data or transmission lines from over-voltage transients and ESD damage.

**MARKING CODE: CTV4** 

#### **FEATURES:**

- · Low capacitance
- · Low clamping voltage
- Protects four I/O lines
- Protects supply voltage rail

SYMBOL		UNITS
$V_{I}$	5.5	V
$V_{ESD}$	15	kV
V <sub>ESD</sub>	8.0	kV
$T_{.l}$ , $T_{sta}$	-55 to +150	°C

#### **ELECTRICAL CHARACTERISTICS:** (T<sub>A</sub>=25°C)


Maximum Reverse Stand-Off Voltage	Rev Break Volt	mum erse down age o pin 2	Rev Leal Cur	mum erse kage rent o pin 2	Volt 8x2	mum pping tage 0µs pin 2	Maximum Off State Junction Capacitance I/O to GND (V <sub>R</sub> =0, f=1.0MHz)	Maximum Off State Junction Capacitance I/O to I/O (V <sub>R</sub> =0, f=1.0MHz)
V <sub>RWM</sub>	v <sub>z</sub> @	D IZ	I <sub>R</sub> @	V <sub>RWM</sub>	v <sub>c</sub> @	D I <sub>PP</sub>	CJ	CJ
V	٧	mA	μΑ	V	V	Α	pF	pF
5.0	6.0	1.0	5.0	5.0	12	1.0	1.2	0.6

#### CMXTVS5-4


### SURFACE MOUNT SILICON LOW CAPACITANCE **QUAD TVS/DIODE ARRAY**



#### **SOT-26 CASE - MECHANICAL OUTLINE**



#### **PIN CONFIGURATION**



DIMENSIONS							
	INC	HES	MILLIMETERS				
SYMBOL	MIN	MAX	MIN	MAX			
Α	0.004	0.007	0.11	0.19			
В	0.016	-	0.40	-			
С	-	0.004	-	0.10			
D	0.039	0.047	1.00	1.20			
E	0.074	0.075	1.88	1.92			
F	0.037	0.038	0.93	0.97			
G	0.102	0.118	2.60	3.00			
Н	0.059	0.067	1.50	1.70			
	0.0	16	0.41				
J	0.110	0.118	2.80	3.00			
0 0.110 0.110 2.00 0.00							

SOT-26 (REV: R2)

#### **LEAD CODE:**


- 1) I/O 1
- 2) Ground 3) I/O 2 4) I/O 3

- 5) Supply Voltage
- 6) I/O 4

MARKING CODE: CTV4

R2 (6-April 2015)

#### CMXTVS5-4





#### **SERVICES**

- · Bonded Inventory
- · Custom Electrical Screening
- Custom Electrical Characteristic Curves
- SPICE Models
- Custom Packaging
- Package Base Options
- Custom Device Development/Multi Discrete Modules (MDM™)
- · Bare Die Available for Hybrid Applications

**LIMITATIONS AND DAMAGES DISCLAIMER:** In no event shall Central be liable for any collateral, indirect, punitive, incidental, consequential, or exemplary damages in connection with or arising out of a purchase order or contract or the use of products provided hereunder, regardless of whether Central has been advised of the possibility of such damages. Excluded damages shall include, but not be restricted to: cost of removal or reinstallation, rework, ancillary costs to the procurement of substitute products, loss of profits, loss of savings, loss of use, loss of data, or business interruption. No claim, suit, or action shall be brought against Central more than two (2) years after the related cause of action has occurred.

In no event shall Central's aggregate liability from any warranty, indemnity, or other obligation arising out of or in connection with a purchase order or contract, or any use of any Central product provided hereunder, exceed the total amount paid to Central for the specific products sold under a purchase order or contract with respect to which losses or damages are claimed. The existence of more than one (1) claim against the specific products sold to Buyer under a purchase order or contract shall not enlarge or extend this limit.

Buyer understands and agrees that the foregoing liability limitations are essential elements of a purchase order or contract and that in the absence of such limitations, the material and economic terms of the purchase order or contract would be substantially different.

R2 (6-April 2015)