



1. Mechanical Dimensions:



2. Schematic:



3. Electrical Specifications: @25°C

OCL: 4.7uH±20% @200KHz, 0.25V

Q: 30 Min @100KHz, 0.25V

DCR: 14.5 mOhms Typ, 15.5 mOhms Max

Isat: 14A (Based on 20% drop in OCL)

Irms: 8A (Based on 40°C Temp Rise)

Notes:

1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: > 28%
4. Insulation System: Class F 155°C. UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to +125°C
6. Storage Temperature Range: -55°C to +125°C
7. Aqueous wash compatible
8. SMD Lead Coplanarity: ±0.004"(0.102mm)
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component
11. Recommended IR Reflow peak temp of 250C Max.
12. Outsourced item processed & controlled under XFMRS QA system

DOC. REV: A/2

XFMRS Inc www.XFMRS.com	Title: INDUCTOR		
	UNLESS OTHERWISE SPECIFIED	P/N: XFHCL11-4R7M	REV. A
TOLERANCES: .xxx ±0.25 Dimensions in MM	DWN.	Yuan	Jul-02-13
	CHK.	YK Liao	Jul-02-13
SHEET 1 OF 1	APP.	BSJ	Jul-02-13