



# IQ05-0B8PS-ZU1

IQY

**INDUCTIVE PROXIMITY SENSORS**

**SICK**  
Sensor Intelligence.



### Ordering information

| Type           | Part no. |
|----------------|----------|
| IQ05-0B8PS-ZU1 | 6020161  |

Other models and accessories → [www.sick.com/IQY](http://www.sick.com/IQY)



### Detailed technical data

#### Features

|  |                     |
|--|---------------------|
| <b>Housing</b>                             | Rectangular         |
| <b>Dimensions (W x H x D)</b>              | 5 mm x 25 mm x 5 mm |
| <b>Sensing range <math>S_n</math></b>      | 0.8 mm              |
| <b>Safe sensing range <math>S_a</math></b> | 0.648 mm            |
| <b>Installation type</b>                   | Flush               |
| <b>Switching frequency</b>                 | 5,000 Hz            |
| <b>Connection type</b>                     | Cable, 3-wire, 2 m  |
| <b>Switching output</b>                    | PNP                 |
| <b>Output function</b>                     | NO                  |
| <b>Electrical wiring</b>                   | DC 3-wire           |
| <b>Enclosure rating</b>                    | IP67 <sup>1)</sup>  |

<sup>1)</sup> According to EN 60529.

#### Mechanics/electronics

|  |                       |
|--|-----------------------|
| <b>Supply voltage</b>                          | 10 V DC ... 30 V DC   |
| <b>Ripple</b>                                  | ≤ 20 % <sup>1)</sup>  |
| <b>Voltage drop</b>                            | ≤ 2 V <sup>2)</sup>   |
| <b>Current consumption</b>                     | ≤ 10 mA <sup>3)</sup> |
| <b>Time delay before availability</b>          | ≤ 10 ms               |
| <b>Hysteresis</b>                              | 1 % ... 10 %          |
| <b>Reproducibility</b>                         | ≤ 1.5 % <sup>4)</sup> |
| <b>Temperature drift (of <math>S_n</math>)</b> | ± 10 %                |

<sup>1)</sup> Of  $V_S$ .

<sup>2)</sup> At  $I_a$  max.

<sup>3)</sup> Without load.

<sup>4)</sup>  $U_b = 20$  V DC ... 30 V DC,  $T_a = 23$  °C ± 5 °C.

|   |                                  |
|---|----------------------------------|
| <b>EMC</b>                              | According to EN 60947-5-2        |
| <b>Continuous current I<sub>a</sub></b> | ≤ 200 mA                         |
| <b>Cable material</b>                   | PUR                              |
| <b>Conductor size</b>                   | 0.06 mm <sup>2</sup>             |
| <b>Short-circuit protection</b>         | ✓                                |
| <b>Reverse polarity protection</b>      | ✓                                |
| <b>Power-up pulse protection</b>        | ✓                                |
| <b>Shock and vibration resistance</b>   | 30 g, 11 ms / 10 ... 55 Hz, 1 mm |
| <b>Ambient operating temperature</b>    | -25 °C ... +70 °C                |
| <b>Housing material</b>                 | Metal, Chrome-plated brass       |
| <b>Sensing face material</b>            | Plastic, Polyester               |

1) Of V<sub>S</sub>.

2) At I<sub>a</sub> max.

3) Without load.

4) U<sub>b</sub> = 20 V DC ... 30 V DC, T<sub>a</sub> = 23 °C ± 5 °C.

### Reduction factors

|                                   |  |
|-----------------------------------|--|
| <b>Note</b>                       | The values are reference values which may vary |
| <b>Stainless steel (V2A, 304)</b> | Approx. 0.85                                   |
| <b>Aluminum (Al)</b>              | Approx. 0.6                                    |
| <b>Copper (Cu)</b>                | Approx. 0.6                                    |
| <b>Brass (Br)</b>                 | Approx. 0.7                                    |

### Installation note

|               |                                       |
|---------------|---------------------------------------|
| <b>Remark</b> | Associated graphic see "Installation" |
| <b>A</b>      | 0.8 mm                                |
| <b>B</b>      | 0 mm                                  |
| <b>C</b>      | 5 mm                                  |
| <b>D</b>      | 2.4 mm                                |
| <b>E</b>      | 0 mm                                  |
| <b>F</b>      | 7 mm                                  |
| <b>G</b>      | 3.3 mm                                |


### Classifications

|                     |          |
|---------------------|----------|
| <b>ECl@ss 5.0</b>   | 27270101 |
| <b>ECl@ss 5.1.4</b> | 27270101 |
| <b>ECl@ss 6.0</b>   | 27270101 |
| <b>ECl@ss 6.2</b>   | 27270101 |
| <b>ECl@ss 7.0</b>   | 27270101 |
| <b>ECl@ss 8.0</b>   | 27270101 |
| <b>ECl@ss 8.1</b>   | 27270101 |
| <b>ECl@ss 9.0</b>   | 27270101 |
| <b>ETIM 5.0</b>     | EC002714 |
| <b>ETIM 6.0</b>     | EC002714 |

UNSPSC 16.0901


39122230

Installation note




Connection diagram

cd-001



Dimensional drawing (Dimensions in mm (inch))

IQ05



## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)