

GR160MT12D

1200 V SiC MOSFET



Silicon Carbide Power MOSFET


N-Channel Enhancement Mode

V_{DS}	=	1200 V
$I_D @ 25^\circ C$	=	20 A
$R_{DS(ON)}$	=	160 mΩ

Features

- 150 °C Maximum Operating Temperature
- High blocking voltage with low On-resistance
- Low output capacitance and gate charge
- Normally-OFF operation at all temperatures
- Halogen free, RoHS compliant

Package



TO-247-3L

Advantages

- Reduced switching losses and minimum gate ringing
- High system efficiency
- Increased power density
- Increased system switching frequency

Applications

- EV Battery Chargers
- Switched-Mode Power Supply (SMPS)
- Solar Inverters
- Renewable Energy
- Motor Drives
- Induction Heating
- Uninterruptible Power Supply (UPS)

Maximum Ratings at $T_C = 25^\circ C$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Drain - Source Voltage	V_{DSmax}	$V_{GS} = 0 \text{ V}$, $I_D = 10 \mu\text{A}$	1200	V
Gate - Source Voltage (dynamic) ¹	V_{GSmax}	AC ($f > 1 \text{ Hz}$)	-10/+25	V
Gate - Source Voltage (static) ²	V_{GSop}	Static	-5/+20	V
Operating Junction and Storage Temperature	T_J , T_{stg}		-55 to +150	°C

Electrical Characteristics at $T_C = 25^\circ C$, unless otherwise specified

Parameter	Symbol	Conditions	Value			Unit
			Min.	Typical	Max.	
Drain - Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0 \text{ V}$, $I_D = 10 \mu\text{A}$	1200			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}$, $I_D = 5 \text{ mA}$		2.6		V
		$V_{DS} = V_{GS}$, $I_D = 5 \text{ mA}$, $T_J = 150^\circ C$		1.8		
Drain - Source Leakage Current	I_{DSS}	$V_{DS} = 1200 \text{ V}$, $V_{GS} = 0 \text{ V}$	0.2			μA
		$V_{DS} = 1200 \text{ V}$, $V_{GS} = 0 \text{ V}$, $T_J = 150^\circ C$	4			
Gate - Source Leakage Current	I_{GSS}	$V_{GS} = 20 \text{ V}$, $V_{DS} = 0 \text{ V}$			100	nA
		$V_{GS} = 20 \text{ V}$, $I_D = 10 \text{ A}$	160			
Drain - Source On-State Resistance	$R_{DS(on)}$	$V_{GS} = 20 \text{ V}$, $I_D = 10 \text{ A}$, $T_J = 150^\circ C$	225			mΩ
Input Capacitance	C_{iss}	$V_{GS} = 0 \text{ V}$, $V_{DS} = 1000 \text{ V}$	520			pF
Output Capacitance	C_{oss}	$f = 1 \text{ MHz}$	45			pF
Reverse Transfer Capacitance	C_{rss}	$V_{AC} = 25 \text{ mV}$	3			pF

Reverse Diode Characteristics at $T_C = 25^\circ C$, unless otherwise specified

Parameter	Symbol	Conditions	Value			Unit
			Min.	Typical	Max.	
Diode Forward Voltage	V_{SD}	$V_{GS} = -4 \text{ V}$, $I_D = 5 \text{ A}$	3.3			V
		$V_{GS} = -4 \text{ V}$, $I_D = 5 \text{ A}$, $T_J = 150^\circ C$	3.1			
Continuous Diode Forward Current	I_S	$V_{GS} = -4 \text{ V}$		20		A