



# 4 Section Bandpass Filter With SMA Female Connectors Operating From 902 MHz To 928 MHz With a 26 MHz Passband

## TECHNICAL DATA SHEET

PE8700

# 4 Section Bandpass Filter With SMA Female Connectors Operating From 902 MHz To 928 MHz With a 26 MHz Passband

### Configuration

Design	Combline Filter
Connector 1	SMA Female
Connector 2	SMA Female
Passband Frequency Range, MHz	902 to 928

#### **Electrical Specifications**

ouriour opoornioutronio	
Passband Minimum Frequency, MHz	902
Passband Maximum Frequency, MHz	928
Impedance, Ohms	50
Maximum Insertion Loss, dB	1.5
Passband Maximum VSWR	1.5:1
Maximum Input Power, Watts	5
Rejection at 815 MHz	50 dB
Rejection at 1.015 GHz	50 dB

## **Mechanical Specifications**

**Connector 1** 

Type SMA Female

Connector 2

Type SMA Female

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

#### **Plotted and Other Data**

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/4-section-band-pass-filter-902-mhz-928-mhz-passband-26-mhz-pe8700-p.aspx

4 Section Bandpass Filter With SMA Female Connectors Operating From 902 MHz To 928 MHz With a 26 MHz Passband from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



# PE8700 CAD Drawing

4 Section Bandpass Filter With SMA Female Connectors Operating From 902 MHz To 928 MHz With a 26 MHz Passband

