



ELECTRO-OPTICAL C	CHARACTERISTICS	$T_A = 25^{\circ}C$	f = 20mA
-------------------	-----------------	---------------------	----------

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		585		nm	
FORWARD VOLTAGE		2.1	2.5	V f	
REVERSE VOLTAGE	5.0			٧r	I <sub>r</sub> =100μΑ
AXIAL INTENSITY		30		mcd	$I_f = 20 \text{mA}$
VIEWING ANGLE		60		2x theta	
EMITTED COLOR:	YELLOW				
EPOXY LENS FINISH:	YELLOW	DIFFUSED			

## LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	- 1.2	mW/*C
OPERATING, STORAGE TEMP.	-40 TO +85	•C
SOLDERING TEMP.	+ 260	•С
2.0mm FROM BODY	3	SEC. MAX

<sup>\*</sup> t<10µS

## NOTES:

- 1. SSL-LX509F3YD, YELLOW LED.
- 2. SSH-LXH600 HOLDER, BLACK.
- 3. ANODE LEAD: LXP-WST24RDTOC, 24 AWG STRANDED, TOP OVERCOAT, RED INSULATION, CUT 160mm LONG, STRIP 2mm BOTH ENDS.
- 4. CATHODE LEAD: LXP-WST24BLTOC, 24 AWG STRANDED, TOP OVERCOAT, BLACK INSULATION, CUT 160mm LONG, STRIP 2mm BOTH ENDS.
- 5. MOLEX 08-50-0114 OR EQUIVALENT.

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MN= +DECIMAL PRECISION UNCONTROLLED DOCUMENT



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538 WEB: WWW.LUMEX.COM

T-5mm (T-1 3/4) LED PANEL MOUNT INDICATOR, 585nm LED, YELOW DIFFUSED LENS, /W 6" WIRE LEADS.

\*\*THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.\*\*

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

)	ION CIVO CIVITI O LELLO DO COMETTI				
	DATE:	07.05.0	01	DRAWN BY:	CT
	PAGE:	1 OF	1	CHKD BY:	KF
	SCALE:	N/A		APRVD BY:	SS
	UNIT: mm [INCH]		Po		