PHŒNIX CONTACT

Electronic housing - DCS 5,7 M C O C 1 7035 - 2203172

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Display housing, 5.7", light gray, central window, front level, consisting of two half shells, four front plates with screws

Why buy this product

- ☑ Item belongs to the DCS product range
- ☑ Display housings for mobile and stationary operator panels
- ☑ Integration of TFT display and membrane keypads
- ☑ Degree of protection: up to IP54
- ☑ Temperature range: -20°C to +50°C
- ☑ Shock-resistant ABS plastic
- ☑ Flammability rating UL 94-V0

RoHS

Key Commercial Data

Packing unit	2 STK
GTIN	4 055626 377285
GTIN	4055626377285

Technical data

General

Housing type	Display housing
Housing material	ABS
Color (RAL)	light gray

Dimensions

Width	224 mm
Height	157 mm
Depth	40 mm

Standards and Regulations

Electronic housing - DCS 5,7 M C O C 1 7035 - 2203172

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0

Drawings

Dimensional drawing

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com