


G5NB-EL

PCB Power Relay

A slim compact Relay with 7 A switching capacity

- 7 A (250 VAC), 5 A (30 VDC) high capacity switching with compact size.
- Minimum 200,000 operations durability at 5 A (250 VAC) switching.
- IEC/EN 60335-1 conformed.
- Ambient operating temperature: max. 85 C

RoHS Compliant



Model Number Legend

G5NB- - -

1 2 3 4 5

- | | |
|---|---|
| <p>1. Number of Poles
1 : 1-pole</p> <p>2. Contact Form
A : SPST-NO (1a)</p> <p>3. Enclosure rating
4 : Fully sealed</p> | <p>4. Classification
EL : High capacity and electrical durability</p> <p>5. Conformity standard
HA : IEC/EN 60335-1 conformed</p> |
|---|---|

Application Examples

- Home appliances
- Industrial equipment
- Building automation

G5NB-EL

Ordering Information

Classification	Item Contact form	Enclosure rating	Model	Rated coil voltage	Minimum packing unit
Single stable relay	SPST-NO (1a)	Fully Sealed	G5NB-1A4-EL-HA	12, 24 VDC	100 pcs/Tray

Note. When ordering, add the rated coil voltage to the model number.

Example: G5NB-1A4-EL-HA DC12

Rated coil voltage

However, the notation of the coil voltage on the product case as well as on the packing will be marked as @@ VDC.

Ratings

Coil

Item Rated voltage	Rated current (mA)	Coil resistance (Ω)	Must operate voltage (V)	Must release voltage (V)	Max. voltage (V)	Power consumption (mW)
			% of rated voltage			
12 VDC	16.7	720	75% max.	10% min.	160% (at 23°C)	Approx. 200
24 VDC	8.3	2,880				

Note 1. The rated current and coil resistance are measured at a coil temperature of 23°C with a tolerance of ±10%.

Note 2. The operating characteristics are measured at a coil temperature of 23°C.

Note 3. The "Max. voltage" is the maximum voltage that can be applied to the relay coil.



Contacts

Item	Load	Resistive load
Contact Type		Single
Contact material		Ag-alloy (Cd free)
Rated load		5 A at 250 VAC, 7 A at 250 VAC
		5 A at 30 VDC
Rated carry current		5 A at DC, 7 A at AC
Max. switching voltage		250 VAC, 30 VDC
Max. switching current		5 A at DC, 7 A at AC


■Dimensions

(Unit: mm)


G5NB-1A4-EL-HA



PCB Mounting Holes
(Bottom View)
Tolerance: ± 0.1 mm



**Terminal Arrangement/
Internal Connections**
(Bottom View)



(No coil polarity)

■Approved Standards

The approval rating values for overseas standards are different from the performance values determined individually. Confirm the values before use.

●UL Recognized: (File No. E41515)

CSA Certified: (File No. LR31928)

Model	Contact form	Coil ratings	Contact ratings	Number of test operations
G5NB-1A4-EL-HA	SPST-NO (1a)	12 to 24V DC	7A 250V AC (General Purpose) 85 C	30,000
			5A 250V AC (General Purpose) 85 C	50,000
			5A 30V DC (Resistive) 85 C	6,000

●EN/IEC, VDE Certified (Certificate No. 137575)

Model	Contact form	Coil ratings	Contact ratings	Number of test operations
G5NB-1A4-EL-HA	SPST-NO (1a)	12, 24V DC	7A 250V AC (Resistive) 85°C	10,000
			5A 30V DC (Resistive) 85 C	

■Precautions

●Please refer to “PCB Relays Common Precautions” for correct use.

■Other data

Creepage distance	6.0 mm
Clearance distance	6.0 mm
Insulation Material Group	III a
Type of insulation coil-contact circuit	Reinforced
open contact circuit	Micro disconnection
Rated Insulation Voltage	250V
Pollution degree	3
Rated voltage system	250V
Overvoltage category	III
Category of protection according to IEC 61810-1	RT III
Glow wire according to IEC 60335-1	<HA Models only> GWT 750°C min. (IEC 60695-2-11) / GWF1 850°C min. (IEC 60695-2-12)
Tracking Index of relay base	PTI 250V min. (housing Parts)
Flammability class according to UL94	V-0

· Application examples provided in this document are for reference only. In actual applications, confirm equipment functions and safety before using the product.
· Consult your OMRON representative before using the product under conditions which are not described in the manual or applying the product to nuclear control systems, railroad systems, aviation systems, vehicles, combustion systems, medical equipment, amusement machines, safety equipment, and other systems or equipment that may have a serious influence on lives and property if used improperly. Make sure that the ratings and performance characteristics of the product provide a margin of safety for the system or equipment, and be sure to provide the system or equipment with double safety mechanisms.

Note: Do not use this document to operate the Unit.