

GTT3455

P-CHANNEL ENHANCEMENT MODE POWER MOSFET

| | |
|---------------------|-------|
| BV _{DSS} | -30V |
| R _{DS(ON)} | 100mΩ |
| I _D | -4.0A |


Description

The GTT3455 utilized advanced processing techniques to achieve the lowest possible on-resistance, extremely efficient and cost-effectiveness device.



The GTT3455 is universally used for all commercial-industrial surface mount applications.

Features

- *Fast Switching Characteristic
- *Lower Gate Charge
- *Small Footprint & Low Profile Package



Package Dimensions



| REF. | Millimeter | | REF. | Millimeter | |
|------|------------|------|------|------------|------|
| | Min. | Max. | | Min. | Max. |
| A | 1.10 MAX. | | L | 0.45 REF. | |
| A1 | 0 | 0.10 | L1 | 0.60 REF. | |
| A2 | 0.70 | 1.00 | θ | 0° | 10° |
| c | 0.12 REF. | | b | 0.30 | 0.50 |
| D | 2.70 | 3.10 | e | 0.95 REF. | |
| E | 2.60 | 3.00 | e1 | 1.90 REF. | |
| E1 | 1.40 | 1.80 | | | |

Absolute Maximum Ratings

| Parameter | Symbol | Ratings | Unit |
|--|-----------------------------------|------------|------|
| Drain-Source Voltage | V _{DS} | -30 | V |
| Gate-Source Voltage | V _{GS} | ±20 | V |
| Continuous Drain Current ³ | I _D @TA=25°C | -4 | A |
| Continuous Drain Current ³ | I _D @TA=70°C | -3.3 | A |
| Pulsed Drain Current ¹ | I _{DM} | -20 | A |
| Power Dissipation | P _D @TA=25°C | 2 | W |
| Linear Derating Factor | | 0.016 | W/°C |
| Operating Junction and Storage Temperature Range | T _j , T _{stg} | -55 ~ +150 | °C |

Thermal Data

| Parameter | Symbol | Ratings | Unit |
|---|--------------------|---------|------|
| Thermal Resistance Junction-ambient ³ Max. | R _{thj-a} | 62.5 | °C/W |

Electrical Characteristics(T_j = 25°C Unless otherwise specified)

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Test Conditions |
|--|--------------------------------|------|-------|------|------|--|
| Drain-Source Breakdown Voltage | BV _{DSS} | -30 | - | - | V | V _{GS} =0, I _D =-250uA |
| Breakdown Voltage Temperature Coefficient | $\Delta BV_{DSS} / \Delta T_j$ | - | -0.02 | - | V/°C | Reference to 25°C, I _D =-1mA |
| Gate Threshold Voltage | V _{GS(th)} | -1.0 | - | -3.0 | V | V _{DS} =V _{GS} , I _D =-250uA |
| Forward Transconductance | g _{fs} | - | 6 | - | S | V _{DS} =-5V, I _D =-4.0A |
| Gate-Source Leakage Current | I _{GSS} | - | - | ±100 | nA | V _{GS} = ±20V |
| Drain-Source Leakage Current(T _j =25°C) | I _{DSS} | - | - | -1 | uA | V _{DS} =-30V, V _{GS} =0 |
| Drain-Source Leakage Current(T _j =55°C) | | - | - | -25 | uA | V _{DS} =-24V, V _{GS} =0 |
| Static Drain-Source On-Resistance ² | R _{DS(ON)} | - | - | 100 | mΩ | V _{GS} =-10V, I _D =-3.5A |
| | | - | - | 170 | | V _{GS} =-4.5V, I _D =-2.7A |
| Total Gate Charge ² | Q _g | - | 5.5 | 8.8 | nC | I _D =-4.0A V _{DS} =-24V V _{GS} =-4.5V |
| Gate-Source Charge | Q _{gs} | - | 1 | - | | |
| Gate-Drain ("Miller") Charge | Q _{gd} | - | 2.6 | - | | |
| Turn-on Delay Time ² | T _{d(on)} | - | 7 | - | ns | V _{DS} =-15V I _D =-1A V _{GS} =-10V R _G =3.3Ω R _D =15Ω |
| Rise Time | T _r | - | 6 | - | | |
| Turn-off Delay Time | T _{d(off)} | - | 18 | - | | |
| Fall Time | T _f | - | 4 | - | | |
| Input Capacitance | C _{iss} | - | 400 | 640 | pF | V _{GS} =0V V _{DS} =-25V f=1.0MHz |
| Output Capacitance | C _{oss} | - | 90 | - | | |
| Reverse Transfer Capacitance | C _{rss} | - | 30 | - | | |

Source-Drain Diode

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Test Conditions |
|------------------------------------|-----------------|------|------|------|------|---|
| Forward On Voltage ² | V _{SD} | - | - | -1.2 | V | I _S =-1.6A, V _{GS} =0V |
| Reverse Recovery Time ² | T _{rr} | - | 21 | - | ns | I _S =-4.0A, V _{GS} =0V di/dt=100A/μs |
| Reverse Recovery Charge | Q _{rr} | - | 14 | - | nC | |

Notes: 1. Pulse width limited by Max. junction temperature.

2. Pulse width ≤ 300us, duty cycle ≤ 2%.

3. Surface mounted on 1 in² copper pad of FR4 board; 156°C/W when mounted on Min. copper pad.

Characteristics Curve




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance v.s. Gate Voltage




Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristics of Reverse Diode




Fig 6. Gate Threshold Voltage v.s. Junction Temperature




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Switching Time Waveform




Fig 12. Gate Charge Waveform

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- Taiwan: No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- China: (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165