

Customer Information Sheet

DRAWING No.: S2751-46R

SHEET 2 OF 2


IF IN DOUBT - ASK

©




NOT TO SCALE

THIRD ANGLE PROJECTION



ALL DIMENSIONS IN mm



SPECIFICATIONS:
FINISH:
4μ MIN 100% TIN OVER 2μ MIN NICKEL
ELECTRICAL:
CURRENT RATING = 3.5A
CONTACT RESISTANCE = 20mΩ MAX
ENVIRONMENTAL:
OPERATING TEMPERATURE = -55°C TO +125°C



NOTES:
1. QUANTITY OF COMPONENTS PER REEL = 2500.



SB	I	02.04.15	12882
NAME	ISS.	DATE	C/NOTE
APPROVED:		S.BENNETT	
CHECKED:		M.PLESTED	
DRAWN:		S.BENNETT	
CUSTOMER REF.:			
ASSEMBLY DRG:			

www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.50mm
X.XX = ±0.10mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL:
BRASS
0.20mm THICK

FINISH: SEE ABOVE

S/AREA: 15.6 mm²

TITLE:
SMT TEST TERMINAL

DRAWING NUMBER:
S2751-46R

SHT 2 OF 2