

51

5,08 R

Direct connectors for insert cards, pitch 2.5/2.54/5.0/ 5.08 mm






Socket board for direct mating, with solder pins

State: Phasing out

51

5,08 R



Environmental conditions

Temperature range -25 °C/+100 °C

Materials

Insulating body PPO
Contact spring CuSn, pre-nickel and tin-plated

Mechanical data

Mating with Leiterplatte 1,5 ± 0,14 mm

Electrical data (at T_{amb} 20 °C)

Contact resistance ≤ 3 mΩ
Rated current 5 A
Rated voltage 250 V AC
Rated impulse voltage ≥ 3,0 kV

Associated products

Accessories

☞ F ☞ FD ☞ FF
☞ FL ☞ SP 3

51

5,08 R

| Designation | Pole Number | PU (Pieces) | MDQ (Pieces) |
|-------------|-------------|-------------|--------------|
| 5,08 R 03 | 3 | 200 | 5000 |
| 5,08 R 04 | 4 | 200 | 5000 |
| 5,08 R 05 | 5 | 200 | 5000 |
| 5,08 R 06 | 6 | 200 | 5000 |
| 5,08 R 07 | 7 | 200 | 5000 |
| 5,08 R 08 | 8 | 200 | 5000 |
| 5,08 R 09 | 9 | 200 | 5000 |
| 5,08 R 10 | 10 | 200 | 5000 |
| 5,08 R 11 | 11 | 200 | 5000 |
| 5,08 R 12 | 12 | 200 | 5000 |
| 5,08 R 13 | 13 | 200 | 5000 |
| 5,08 R 14 | 14 | 200 | 5000 |
| 5,08 R 15 | 15 | 200 | 5000 |
| 5,08 R 16 | 16 | 200 | 5000 |
| 5,08 R 17 | 17 | 200 | 5000 |
| 5,08 R 18 | 18 | 200 | 5000 |
| 5,08 R 19 | 19 | 200 | 5000 |
| 5,08 R 20 | 20 | 200 | 5000 |
| 5,08 R 21 | 21 | 200 | 5000 |
| 5,08 R 22 | 22 | 200 | 5000 |
| 5,08 R 23 | 23 | 200 | 5000 |
| 5,08 R 24 | 24 | 200 | 5000 |
| 5,08 R 25 | 25 | 200 | 5000 |
| 5,08 R 26 | 26 | 200 | 5000 |
| 5,08 R 27 | 27 | 200 | 5000 |
| 5,08 R 28 | 28 | 200 | 5000 |
| 5,08 R 29 | 29 | 200 | 5000 |
| 5,08 R 30 | 30 | 200 | 5000 |
| 5,08 R 31 | 31 | 200 | 5000 |
| 5,08 R 32 | 32 | 200 | 5000 |
| 5,08 R 33 | 33 | 200 | 5000 |

Packaging:

in bulk, in a cardboard box