

CC15-2403SFH-E



<b>Sales Region</b>	Worldwide
<b>Series</b>	CC-P-E
<b>Status</b>	Production
<b>Option</b>	DIP type High withstand voltage Parallel operation
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	<a href="#">Please refer to here.</a>
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



**Electrical Characteristics**

Rated Input Voltage[DC]	24V
Input Voltage Range[DC]	18 to 36V
Efficiency	89% Typ.
Rated Output Voltage[DC]	3.3V
Output Voltage Range[DC]	Fixed
Maximum Output Current	
Maximum Ripple Noise	50mV
Maximum Output Power	15W
Withstanding Voltage1	Input - Output: 1500VDC: 1min.
Withstanding Voltage2	
Withstanding Voltage3	

**Cases Shape & Size**

Case'□' shape	On board/Power module
Width(W)	38.2mm Nom.
Height(H)	5mm Nom.
Depth(D)	27.6mm Nom.
Weight	10g Typ.
Industry Standard Size	
Terminal Style	DIP

**Other**

Operating Temp. Range	-40 to 85°C
Isolated / Non-isolated	Isolated
Feature	
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 (C-UL) EN60950-1 (NEMKO)

Remarks

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.